

South Dakota Ambient Air Monitoring Annual Plan 2020



**South Dakota
Department of Environment and
Natural Resources
Air Quality Program**

Table of Contents

Section	Page
Table of Contents	i
List of Tables	iv
List of Figures.....	v
Executive Summary	vii
1.0 INTRODUCTION.....	1
2.0 AMBIENT AIR MONITORING NETWORK HISTORY	1
3.0 AIR MONITORING GOALS.....	3
4.0 AIR MONITORING PLAN.....	3
4.1 State and Local Air Monitoring Stations.....	5
4.2 Special Purpose Monitoring.....	5
4.3 Prevention of Significant Deterioration Monitoring Sites	5
4.4 Interagency Monitoring of Protected Visual Environments Network.....	5
4.5 Environmental Radiation Network	5
4.6 National Core Multi-Pollutant Site	6
5.0 AMBIENT AIR MONITORING NEEDS AND REQUIREMENTS.....	8
5.1 Monitoring State’s Largest Population Centers	8
5.2 Real Time Data.....	9
5.3 Class I Areas.....	10
5.4 Metropolitan Statistical Areas	10
5.4.1 Required Ozone Monitoring Sites.....	11
5.4.2 Required PM ₁₀ Monitoring Sites	12
5.4.3 Required PM _{2.5} Monitoring Sites.....	13
5.4.4 Required Carbon Monoxide Monitoring Sites.....	14
5.4.5 Required Nitrogen Dioxide Monitoring Sites.....	15
5.4.6 Required Sulfur Dioxide Monitoring Sites	15
5.4.7 Required Lead Monitoring Sites.....	16
5.5 Additional Monitoring.....	17
5.6 Future Monitoring	17
6.0 NETWORK MODIFICATIONS FOR 2020	17
6.1 New Sites	17
6.2 Sites Closed	18
6.3 Modifications.....	18
7.0 REQUEST FOR WAIVER	18
8.0 EQUIPMENT REPLACEMENT PLAN.....	18
8.1 Overview	18

8.2	Data Loggers.....	19
8.3	Manual Particulate Matter Monitors.....	20
8.3.1	<i>Partisol Monitors</i>	20
8.3.2	<i>Hi-Vol PM₁₀ Monitors</i>	21
8.3.3	<i>Speciation PM_{2.5} Monitors</i>	21
8.4	Continuous Particulate Matter Monitors	21
8.4.1	<i>Thermo 5014i BETA Monitors</i>	21
8.4.2	<i>Met One BAM 1020 Monitors</i>	22
8.5	Continuous Gas Analyzers and Calibrators.....	22
8.5.1	<i>Ozone Analyzers</i>	23
8.5.2	<i>Sulfur Dioxide Analyzers</i>	23
8.5.3	<i>Nitrogen Dioxide Analyzers</i>	24
8.5.4	<i>Carbon Monoxide Analyzers</i>	25
8.5.5	<i>Multi-gas/Ozone Calibrators</i>	25
8.6	Meteorological Stations	26
9.0	COMPLIANCE WITH NATIONAL AMBIENT AIR QUALITY STANDARDS ...	26
9.1	Particulate Matter (PM ₁₀).....	26
9.2	Particulate Matter (PM _{2.5}).....	28
9.2.1	<i>PM_{2.5} 24-Hour Standard</i>	28
9.2.2	<i>PM_{2.5} Annual Standard</i>	30
9.3	Lead.....	32
9.4	Ozone.....	32
9.5	Sulfur Dioxide.....	34
9.5.1	<i>Sulfur Dioxide 1-Hour Standard</i>	34
9.5.2	<i>Sulfur Dioxide 3-Hour Secondary Standard</i>	35
9.6	Nitrogen Dioxide	36
9.6.1	<i>Nitrogen Dioxide 1-Hour Standard</i>	36
9.6.2	<i>Nitrogen Dioxide Annual Standard</i>	37
9.7	Carbon Monoxide	38
9.8	2019 High Concentrations Summary	39
9.8.1	<i>PM_{2.5} High Concentration Days</i>	40
9.8.2	<i>PM₁₀ High Concentration Days</i>	40
9.8.3	<i>Ozone High Concentration Days</i>	41
10.0	AIR MONITORING SITE TRENDS	42
10.1	Rapid City Area	42
10.1.1	<i>Rapid City Library Site</i>	43
10.1.2	<i>Rapid City Credit Union Site</i>	46
10.2	Black Hawk Site	52
10.2.1	<i>Black Hawk Site PM₁₀ Data</i>	54
10.2.2	<i>Black Hawk Site Ozone Data</i>	55
10.3	Badlands Site	55
10.3.1	<i>Badlands Site – PM₁₀ Data</i>	57
10.3.2	<i>Badlands Site – PM_{2.5} Data</i>	58

10.3.3	<i>Badlands Site – Sulfur Dioxide Data</i>	<i>59</i>
10.3.4	<i>Badlands Site Ozone Data.....</i>	<i>60</i>
10.3.5	<i>Badlands Site – Nitrogen Dioxide Data</i>	<i>61</i>
10.4	Wind Cave Site.....	62
10.4.1	<i>Wind Cave Site PM₁₀ Data.....</i>	<i>64</i>
10.4.2	<i>Wind Cave Site PM_{2.5} Data</i>	<i>65</i>
10.4.3	<i>Wind Cave Site Ozone Data</i>	<i>66</i>
10.5	SD School Site - Sioux Falls Area	67
10.5.1	<i>SD School Site PM₁₀ Data</i>	<i>70</i>
10.5.2	<i>SD School Site – PM_{2.5} Data.....</i>	<i>71</i>
10.5.3	<i>SD School Site Ozone Data.....</i>	<i>72</i>
10.5.4	<i>SD School Site Sulfur Dioxide Data.....</i>	<i>73</i>
10.5.5	<i>SD School Site Nitrogen Dioxide Data.....</i>	<i>74</i>
10.5.6	<i>SD School Site Carbon Monoxide Data</i>	<i>75</i>
10.6	Fire Station #1 Site – Aberdeen Area.....	76
10.6.1	<i>Fire Station #1 Site PM₁₀ Data</i>	<i>77</i>
10.6.2	<i>Fire Station #1 Site PM_{2.5} Data</i>	<i>79</i>
10.7	Research Farm Site – Brookings Area.....	80
10.7.1	<i>Research Farm Site PM₁₀ Data</i>	<i>81</i>
10.7.2	<i>Research Farm Site PM_{2.5} Data.....</i>	<i>82</i>
10.7.3	<i>Research Farm Site Ozone Data.....</i>	<i>83</i>
10.8	Watertown Site.....	83
10.8.1	<i>Watertown Site PM₁₀ Data.....</i>	<i>85</i>
10.8.2	<i>Watertown Site PM_{2.5} Data</i>	<i>86</i>
10.9	UC #1 Site – Union County	86
10.9.1	<i>UC #1 Site PM₁₀ Data</i>	<i>89</i>
10.9.2	<i>UC #1 Site PM_{2.5} Data.....</i>	<i>89</i>
10.9.3	<i>UC #1 Site Sulfur Dioxide Data.....</i>	<i>90</i>
10.9.4	<i>UC #1 Site – Nitrogen Dioxide Data.....</i>	<i>91</i>
10.9.5	<i>UC #1 Site Ozone Data.....</i>	<i>92</i>
10.10	Pierre Airport Site	93
10.10.1	<i>Pierre Airport Site – PM_{2.5} Data</i>	<i>94</i>
11.0	SPECIAL AIR QUALITY MONITORING.....	95
11.1	PM_{2.5} Speciation Network.....	95
12.0	CONCLUSIONS	97
13.0	REFERENCES.....	97

List of Tables

Table	Page
Table 5-1 – 10 Largest Cities in South Dakota 2010.....	8
Table 5-2 – 10 Counties with the Highest Populations 2010.....	8
Table 5-3 – Minimum Ozone Sites Required	11
Table 5-4 – Minimum PM ₁₀ Sites Required.....	13
Table 5-5 – Minimum PM _{2.5} Sites Required	14
Table 5-6 – Population Weighted Emission Index	16
Table 8-1 - Data Logger Service Records.....	19
Table 8-2 – Partisol Service Record	20
Table 8-3 - 5014 Service Record	21
Table 8-4 - BAM Service Record	22
Table 8-5 - Ozone Analyzers	23
Table 8-6 - Sulfur Dioxide Analyzers.....	24
Table 8-7 - Nitrogen Dioxide Analyzers	24
Table 8-8 - Carbon Monoxide Analyzers	25
Table 8-9 - Multi-gas/Ozone Calibrators.....	25
Table 9-1 – Statewide PM ₁₀ 24-Hour Concentrations	27
Table 9-2 – Statewide PM _{2.5} 24-Hour Concentrations	28
Table 9-3 – Statewide PM _{2.5} Annual Concentrations	30
Table 9-4 – Statewide Ozone 4 th highest Concentrations	33
Table 9-5 – 2019 Statewide Sulfur Dioxide 1-hour Design Values	34
Table 9-6 – Nitrogen Dioxide 1-Hour 98 th Percentile Concentrations	36
Table 9-7 – 2019 High 24-Hour PM _{2.5} Readings.....	40
Table 9-8 - 2019 High 24-Hour PM ₁₀ Readings.....	40
Table 10-1 – Rapid City Library Site Specifics.....	44
Table 10-2 – Rapid City Credit Union Site Specifics.....	47
Table 10-3 – Black Hawk Site Specifics	53
Table 10-4 – Badlands Site Specifics	56
Table 10-5 – Wind Cave Site Specifics	63
Table 10-6 – SD School Site Specifics	68
Table 10-7 – Fire Station #1 Site Specifics	77
Table 10-8 –Research Farm Site Specifics	81
Table 10-9 – Watertown Site Specifics	84
Table 10-10 – UC #1 Site Specifics.....	87
Table 10-11 – Pierre Airport Site Specifics.....	93

List of Figures

Figure	Page
Figure 4-1 – South Dakota Air Monitoring Sites.....	4
Figure 4-2 – SD School Site Area Map	7
Figure 9-1 – 2019 PM _{2.5} Statewide 24-Hour Design Values.....	30
Figure 9-2 – 2019 PM _{2.5} Statewide Annual Design Values.....	31
Figure 10-1 – Rapid City Library Site	44
Figure 10-2 – Rapid City Library Site PM ₁₀ Annual Averages 2019.....	45
Figure 10-3 – Rapid City Library Site PM _{2.5} Annual Averages 2019	46
Figure 10-4 – Rapid City Credit Union Site	47
Figure 10-5 – Rapid City Credit Union Site PM ₁₀ Annual Averages.....	49
Figure 10-6 – Rapid City Credit Union Site PM _{2.5} Annual Averages	50
Figure 10-7 – Rapid City Credit Union Site Sulfur Dioxide 99 th Percentile 1-hour Averages	51
Figure 10-8 – Rapid City Credit Union Site Nitrogen Dioxide Annual Averages	52
Figure 10-9 – Black Hawk Site.....	53
Figure 10-10 – Black Hawk Site – PM ₁₀ Annual Averages	54
Figure 10-11 – Black Hawk Site Ozone Yearly 4 th Highest 8-hour Averages	55
Figure 10-12 –Badlands Site.....	56
Figure 10-13 – Badlands Site – PM ₁₀ Annual Averages	58
Figure 10-14 – Badlands Site – PM _{2.5} Annual Averages.....	59
Figure 10-15 – Badlands Site – Sulfur Dioxide 99 th Percentile 1-hour Average	60
Figure 10-16 – Badlands Site – Ozone Yearly 4 th Highest 8-hour Averages	61
Figure 10-17 – Badlands Site – Nitrogen Dioxide Annual Averages.....	62
Figure 10-18 – Wind Cave Site	63
Figure 10-19 - Wind Cave Site – PM ₁₀ Annual Averages.....	65
Figure 10-20 - Wind Cave Site – PM _{2.5} Annual Averages	66
Figure 10-21 – Wind Cave Ozone Yearly 4 th Highest 8-hour Averages	67
Figure 10-22 – SD School Site	68
Figure 10-23 – SD School Site – PM ₁₀ Annual Averages	71
Figure 10-24 – SD School Site – PM _{2.5} Annual Averages	72
Figure 10-25 – SD School Site - Ozone Yearly 4 th Highest 8-Hour Averages	73
Figure 10-26 – SD School Site – Sulfur Dioxide Yearly 1-hour 99 th Percentile.....	74
Figure 10-27 – SD School Site – Nitrogen Dioxide Annual Averages	75
Figure 10-28 – SD School Site – Carbon Monoxide 8-hour averages	76
Figure 10-29 – Aberdeen’s Fire Station #1 Site	76
Figure 10-30 – Fire Station #1 Site – PM ₁₀ Annual Averages	78
Figure 10-31 – Fire Station #1 Site – PM _{2.5} Annual Averages.....	79
Figure 10-32 –Research Farm Site	80
Figure 10-33 –Research Farm Site – PM ₁₀ Annual Averages	82
Figure 10-34 –Research Farm Site – PM _{2.5} Annual Averages	82
Figure 10-35 – Brookings Research Farm Site Ozone Yearly 4 th Highest 8-Hour Averages	83
Figure 10-36 – Watertown Site.....	84

Figure 10-37 – Watertown Site – PM ₁₀ Annual Averages	85
Figure 10-38 – Watertown Site PM _{2.5} Annual Averages.....	86
Figure 10-39 – UC #1 Site.....	87
Figure 10-40 – UC #1 Site – Annual PM ₁₀ Concentrations	89
Figure 10-41 –UC #1 Site – Annual PM _{2.5} Concentrations.....	90
Figure 10-42 –UC #1 Sulfur Dioxide 1-hour Concentrations	91
Figure 10-43 –UC #1 Site – Annual Nitrogen Dioxide Concentrations.....	92
Figure 10-44 – Union County #1 Site Ozone Concentrations	92
Figure 10-45 – Pierre Airport Site	93
Figure 10-46 – Pierre Airport Site – Annual PM _{2.5} Concentrations	94
Figure 11-1 – Average URG Monitor Total Carbon Concentrations	96
Figure 11-2 – Average Nitrate and Sulfate Concentrations.....	96

Executive Summary

The South Dakota Department of Environment and Natural Resources (DENR) develops an annual ambient air monitoring network plan which is a review of the ambient air monitoring network each year as required by Title 40 of the Code of Federal Regulation (CFR), Part 58. All areas of the state are in attainment with the Environmental Protection Agency's (EPA's) National Ambient Air Quality Standards (NAAQS).

The annual plan will be published on the department's air quality website to provide a 30-day public review and comments will be taken so appropriate adjustments can be made to meet the needs of the general public before the annual plan will be finalized. The public review period began on May 27 and ended on June 26, 2020. No comments were received. The annual plan includes the following major sections:

1. Ambient air monitoring goals, plans and needs are in Sections 3.0 through 5.0, respectively;
2. Proposed modifications to the ambient air monitoring network to meet the changing trends, national requirements, and state needs are in Section 6.0;
3. Sampling frequency waivers are identified in Section 7.0;
4. Purchase replacement plan is in Section 8.0;
5. Evaluation of collected data compared to the National Ambient Air Quality Standards is in Section 9.0;
6. Air pollution trends for each site are in Sections 10.0; and
7. Special air quality monitoring is identified in Section 11.0.

The department is planning the following site modifications in 2020 and 2021:

1. Continue replacing older continuous monitors before they become too expensive to repair and as resources allow;
2. Evaluate potential air monitoring sites to replace the Sioux Falls SD School Site and the Rapid City Credit Union Site. The department has been informed that due to changes in ownership these sites may need to be moved;
3. The Aberdeen Fire Station #1 Site was closed at the end of 2019 and the Aberdeen Bus Stop Site was opened to replace it at the beginning of 2020 to allow for the installation and operation of continuous particulate monitors to replace the manual monitors; and
4. An Ozone monitor was added in early 2020 at the Watertown site to expand long-range transport observations farther North along the eastern border of the state.

1.0 INTRODUCTION

The United States Environmental Protection Agency through Title 40 of the Code of Federal Regulation and the Performance Partnership Agreement (PPA) requires the South Dakota Department of Environment and Natural Resources to complete an annual ambient air monitoring plan. EPA's requirements for the annual plan are listed in Title 40 of the Code of Federal Regulations §58.10. The plan will cover a review of the ambient air monitoring sites and determine if the network is meeting the monitoring objectives in Title 40 of the Code of Federal Regulations Part 58, Appendixes A, C, D, and E. The plan will identify needed modifications to the network such as the termination or relocation of a monitor, addition of new parameters, or the establishment of new stations. The plan will update compliance concentrations for comparison to the National Ambient Air Quality Standards and to determine trends for each sampling parameter.

The department is required to take public comments on the plan for 30 days prior to submitting the plan to EPA. The department complied with this requirement by posting this document on the department's Air Quality Program website on May 27, 2020 at the following location for 30 days: <http://denr.sd.gov/des/aq/airprogr.aspx>. No comments were received during the review period. DENR has posted the finalized Annual Plan for 2020 on our webpage at: <http://denr.sd.gov/des/aq/monitoring/state-mo.aspx>.

2.0 AMBIENT AIR MONITORING NETWORK HISTORY

In 1972, South Dakota developed, and EPA approved a State Implementation Plan (SIP) which included the establishment and operation of an ambient air monitoring network for the state. In 1980, South Dakota submitted a revision to its State Implementation Plan to upgrade the program by establishing a network of State and Local Air Monitoring (SLAMS) stations and Special Purpose Monitoring (SPM) stations.

In the past, EPA has changed the National Ambient Air Quality Standards several times. Currently, EPA has established National Ambient Air Quality Standards for Particulate Matter (PM), Sulfur Dioxide (SO₂), Nitrogen Dioxide (NO₂), Ozone, Carbon Monoxide (CO), and Lead.

The particulate matter 10 microns in diameter or less (PM₁₀) standard was set in 1987 setting a 24-hour level of 150 micrograms per cubic meter (ug/m³) and an annual standard of 50 micrograms per cubic meter. In 2006, EPA revoked the annual standard leaving only the 24-hour standard. The department began monitoring for PM₁₀ in 1987, and is currently monitoring PM₁₀ concentrations in Sioux Falls, Brookings, Watertown, Union County, Aberdeen, Badlands National Park, Wind Cave National Park, Black Hawk and Rapid City. The PM₁₀ monitoring network represents the most populated and rural areas of the state. South Dakota's ambient air monitoring network for PM₁₀ has historically demonstrated attainment with the PM₁₀ standards. The particulate matter 2.5 microns in diameter or less (PM_{2.5}) standards for 24-hour and annual levels were set in 1997. EPA revised the PM_{2.5} standard significantly by reducing the 24-hour standard from 65 micrograms per cubic meter to 35 micrograms per cubic meter in 2006. The annual standard was revised from 15 micrograms per cubic meter to 12 micrograms per cubic

meter in 2013. The department began monitoring for PM_{2.5} in 1999 and is currently monitoring PM_{2.5} concentrations in Sioux Falls, Brookings, Watertown, Union County, Aberdeen, Pierre, Badlands National Park, Wind Cave National Park, and Rapid City. The PM_{2.5} monitoring network represents the most populated and rural areas of the state. South Dakota's ambient air monitoring network for PM_{2.5} has historically demonstrated attainment with the PM_{2.5} standards.

EPA set the first Sulfur Dioxide standards in 1971. The primary standards were 140 parts per billion for the 24-hour average and 30 parts per billion (ppb) for the annual average. The secondary standard was 500 parts per billion for the 3-hour average. The Sulfur Dioxide standard was revised in 2010 setting a new primary 1-hour standard of 75 parts per billion and revoking the 24-hour and annual standards. The department began monitoring for Sulfur Dioxide in 1974, using bubbler method samplers. All the bubbler method samplers were closed out in the 1980s because of problems with the test method in cold climates and low concentration levels. In 2002, the program began setting up continuous analyzers and currently operates Sulfur Dioxide analyzers in Sioux Falls, Union County, Badlands National Park, and Rapid City. The Sulfur Dioxide monitoring network represents the highest population areas and rural areas of the state. South Dakota's ambient air monitoring network for Sulfur Dioxide has historically demonstrated attainment with the Sulfur Dioxide standards.

The Nitrogen Dioxide standard was established in 1971 setting an annual average standard of 53 parts per billion. In 2010, EPA revised the standard by adding a one-hour standard of 100 parts per billion. The annual standard was retained without any change in concentration level. The department first tested for Nitrogen Dioxide in 1974, using bubbler method samplers. All the bubbler method samplers were closed out in the 1980s because of problems with the test method in cold climates and low concentration levels. The department started testing again for Nitrogen Dioxide in 2003 and currently operates continuous Nitrogen Dioxide monitors in Sioux Falls, Union County, Badlands National Park, and Rapid City. The Nitrogen Dioxide monitoring network represents the most populated and rural areas of the state. South Dakota's ambient air monitoring network for Nitrogen Dioxide has historically demonstrated attainment with the Nitrogen Dioxide standards.

The ozone standard was established in 1979, setting a 1-hour average standard of 0.120 parts per million (ppm). In 1997, the standard was revised setting an 8-hour average of 0.08 parts per million. In 2008, EPA revised the 8-hour average to 0.075 parts per million. In 2015, EPA set the current 8-hour average at 0.070 parts per million. South Dakota's ambient air monitoring network for ozone was established in 1999 and is currently monitoring concentrations in Sioux Falls, Union County, Brookings, Badlands National Park, Wind Cave National Park, and Black Hawk. The ozone monitoring network represents the highest population and three rural areas of the state. South Dakota's ambient air monitoring network for ozone has historically demonstrated attainment with the ozone standards.

The Carbon Monoxide standard was established in 1971. The primary and secondary standards were 35 parts per million for the 1-hour average and 9 parts per million for the 8-hour average. In 1985, the primary standards were retained without revision and the secondary standards were revoked. The department began monitoring for Carbon Monoxide in 2009 as part of collecting air monitoring data to show background levels for the criteria pollutants prior to the anticipated

construction of the Hyperion Energy Center. Three years of data was collected, and monitoring was discontinued in 2013 because concentrations during the three years of sampling were very low. A second site was added in 2011, at the SD School Site in Sioux Falls as part of the required testing at a National Core (NCore) site. South Dakota's ambient air monitoring network for Carbon Monoxide has historically demonstrated attainment with the Carbon Monoxide standards.

The lead standard was established in 1978, with a concentration of 1.5 micrograms per cubic meter. Testing was done in the 80's and 90's and results showed compliance with the standard. In 2008, the standard was significantly revised setting a concentration level of 0.15 micrograms per cubic meter. EPA made changes to the air monitoring requirements for lead in 2009 to help determine where states would need to test. The final rule did not require lead monitoring at the National Core site and all sources in South Dakota have emission levels less than 0.5 ton per year. Therefore, testing for lead is not required at this time. South Dakota's ambient air monitoring network for lead has historically demonstrated attainment with the lead standard.

Data collected from the ambient air monitoring network is entered into the federal database called the Air Quality System (AQS). Individuals interested in reviewing the air quality data can go to the EPA website at the following address: <http://www.epa.gov/airdata/>

3.0 AIR MONITORING GOALS


The department's Air Quality Program was established with the primary goal of protecting the health, welfare and property of South Dakotans from the detrimental effects of air pollution. The Clean Air Act of 1970 and subsequent amendments define air quality standards for various air pollutants necessary to protect the public from injurious pollution concentrations.

In order to attain and maintain the National Ambient Air Quality Standards, the department developed regulations that restrict air pollution from sources, establishes these restrictions in an air quality permit, requires periodic inspections to ensure compliance, and maintains an ambient air monitoring network to provide air quality information and monitor the success of the Air Quality Program. Based on the ambient monitoring concentrations collected throughout the state, the department's Air Quality Program is meeting its goals.

4.0 AIR MONITORING PLAN

In calendar year 2019, the ambient air monitoring network includes 13 ambient air monitoring sites run by the department. There were three sites in Rapid City, two sites in Pierre, and one site in the remaining eight locations. Figure 4-1 shows a map of the general locations and cities with ambient air monitoring sites in 2019.

Figure 4-1 – South Dakota Air Monitoring Sites



The following types of ambient air monitors and monitoring sites may be operated in South Dakota:

1. State and local air monitoring stations;
2. Special purpose monitors;
3. Prevention of Significant Deterioration (PSD) monitors;
4. Interagency Monitoring of Protected Visual Environments (IMPROVE) sites;
5. Environmental Radiation Network (RadNet) ambient monitoring systems; and
6. National Core multi-pollutant sites.

Ambient air monitoring site files are maintained in the department's Pierre office for the state and local air monitoring stations, special purpose monitoring sites, and the National Core multi-pollutant site. The ambient air monitoring site files are available for public review during normal working hours from 8:00 AM to 5:00 PM each workday. The monitoring site files contain at a minimum the following information for each site:

1. Air Quality System site identification form;
2. Sampling location;
3. Sampling and analysis method;
4. Operating schedule;
5. Monitoring objective and spatial scale;
6. Beginning date of operation; and
7. Site maps.

4.1 State and Local Air Monitoring Stations

A state and local air monitoring station consists of an air monitor for at least one air pollutant parameter selected by the state or local air programs to determine compliance with the National Ambient Air Quality Standards. At the beginning of 2019, 11 of the network's sites were considered a state and local air monitoring station. The sites in the network collected PM₁₀ data at 10 sites, PM_{2.5} data at 10 sites, Sulfur Dioxide and Nitrogen Dioxide at four sites, Ozone at six sites, and Carbon Monoxide at one site.

4.2 Special Purpose Monitoring

Special Purpose Monitoring is a generic term for all monitors not used to determine compliance with the National Ambient Air Quality Standards and used for special studies. The data is reported to EPA, the equipment is EPA or non-EPA designated monitoring methods, and the monitoring data is used for special circumstances or needs. Four of the ambient air monitoring network sites operated special purpose monitoring in 2019. The parameters tested by the special purpose monitoring in South Dakota include:

1. Weather stations at the Black Hawk and SD School sites;
2. PM_{coarse} monitor, Total Reactive Nitrogen (NO_y) analyzer, and PM_{2.5} speciation monitors at the SD School Site; and
3. Radiation monitors operated at the Pierre Quonset and Rapid City National Guard sites.

Particulate matter coarse (PM_{coarse}) is particulate matter 10 microns in diameter or less (PM₁₀) minus particulate matter 2.5 microns in diameter or less (PM_{2.5}).

4.3 Prevention of Significant Deterioration Monitoring Sites

In 2019, no Prevention of Significant Deterioration air monitoring projects were started or completed.

4.4 Interagency Monitoring of Protected Visual Environments Network

Two Interagency Monitoring of Protected Visual Environments sites are being operated by the National Parks Service in South Dakota. The site locations are at the Badlands and Wind Cave National Parks. Data results for parameters collected by the National Park Service can be requested from the following website: <http://views.cira.colostate.edu/fed/QueryWizard/>

4.5 Environmental Radiation Network

The Environmental Radiation Network sites in Pierre and Rapid City are being operated as a part of the national network and are also considered Special Purpose Monitoring Sites. The Pierre Site has been operated since the early 1980s. The state has a limited role in operating the monitor. The state collects the samples and ships the samples to the EPA office of Radiation and Indoor Air. The type of sample collected is airborne particulates and measurements taken are gross beta radiation levels.

In 2009, EPA requested a second site in the state to be in the Rapid City area. The new Radiation Network monitor was installed at the Rapid City National Guard Site on May 7, 2009. The site is operated by the department's Rapid City Regional Office in conjunction with the Rapid City National Guard.

The general objectives of the sampling sites are to provide a means of estimating ambient levels of radioactive pollutants in our environment, to follow trends in environmental radioactivity levels, and to assess the impact of fallout and other intrusions of radioactive materials. Specifically, the Radiation Network monitors were designed to:

1. Provide a direct assessment of the population's intake of radioactive pollutants due to fallout;
2. Provide data for developing a set of dose computational models for specific sources and a national dose computational model to aggregate all sources and determine total population dose;
3. Monitor pathways for significant population exposure from routine, accidental, and terrorist releases of radioactivity from major sources;
4. Provide data for indicating additional sampling needs or other actions required to ensure public health and environmental quality in the event of a major release of radioactivity to the environment; and
5. Serve as a reference for data comparison with other localized and limited monitoring programs.

The radiation data collected at this site may be reviewed at:
<https://www.epa.gov/enviro/radnet-customized-search>


4.6 National Core Multi-Pollutant Site

The National Core multi-pollutant monitoring site will provide data on several pollutants at lower detection levels and replaces the National Air Monitoring Station (NAMS) sites that have existed for several years. Each state's ambient air monitoring network is required to have at least one National Core site. The National Core site addresses the following monitoring objectives:

1. Timely reporting of data to the public through AirNow for air quality forecasting and other public reporting mechanisms;
2. Support development of emission strategies through air quality model evaluation and other observational methods;
3. Accountability of emission strategy progress through tracking long-term trends of criteria and non-criteria pollutants and their precursors;
4. Support long-term health assessments that contribute to ongoing reviews of the National Ambient Air Quality Standards;
5. Compliance through establishing nonattainment/attainment areas by comparison with the National Ambient Air Quality Standards; and
6. Support multiple disciplines of scientific research including public health, atmospheric and ecological.

The National Core site in South Dakota is located on the SD School campus in Sioux Falls, which is identified as the SD School Site (46-099-0008). This site meets the location requirements to be in an urban residential area. Sioux Falls was selected as the National Core site for South Dakota because it is the largest city in the state and is one of the state's fastest growing communities. See Figure 4-2 for an aerial view of the city around the SD School Site.

Figure 4-2 – SD School Site Area Map



At the beginning of 2011, all required parameters were operating at the SD School Site. The SD School Site collects data for trace level Sulfur Dioxide, nitrogen oxides, all reactive oxides of nitrogen, Carbon Monoxide, ozone, PM_{2.5} continuous and filter based manual monitors, PM_{coarse}, PM_{2.5} speciated, PM₁₀ and meteorological parameters of wind speed, wind direction, relative humidity, and ambient temperature.

5.0 AMBIENT AIR MONITORING NEEDS AND REQUIREMENTS

5.1 Monitoring State's Largest Population Centers

South Dakota's industrial base and population centers are typical of the northern plains' states. The largest industry in the state is agriculture. Most of the other industries are in several localized areas. The industries in these locations are typically small (less than 50 employees) and generally do not produce large quantities of air pollutants. Most are considered service-oriented businesses or light industrial. The only heavy industrial facilities are the Big Stone Power Plant in Grant County and the quarry area in Rapid City.

The population distribution of the state follows the general industrial distribution. Most of the state's population of 814,180, from the 2010 Census, lives either on the eastern or western third of South Dakota. Since 2010, there has been a modest population increase in South Dakota of about 8.7% according to estimates of 884,659 done in July 2019. The two largest cities in South Dakota are Sioux Falls and Rapid City located in southeastern and western South Dakota, respectively. The remaining population is primarily spread across the eastern third of the state with the remaining portion of the state sparsely populated. See Table 5-1 for a list of the 10 largest cities and Table 5-2 for a list of the 10 largest counties in the state.

Table 5-1 – 10 Largest Cities in South Dakota 2010

Ranking	City Name	Counties	Population
1	Sioux Falls	Minnehaha/Lincoln	153,888
2	Rapid City	Pennington /Meade	67,956
3	Aberdeen	Brown	26,091
4	Brookings	Brookings	22,056
5	Watertown	Codington	21,482
6	Mitchell	Davison	15,254
7	Yankton	Yankton	14,454
8	Pierre	Hughes	13,646
9	Huron	Beadle	12,592
10	Vermillion	Clay	10,571

Table 5-2 – 10 Counties with the Highest Populations 2010

Ranking	Counties	Population
1	Minnehaha	169,468
2	Pennington	100,948
3	Lincoln	44,828
4	Brown	36,531
5	Brookings	31,965
6	Codington	27,277
7	Meade	25,434
8	Lawrence	24,097
9	Yankton	22,438
10	Davison	19,504

Given South Dakota's population distribution, most of the air monitoring efforts of the state have in the past been concentrated in the areas of high population. Within these areas of high population, monitoring sites are chosen that will determine areas of high pollution concentration, determine if the National Ambient Air Quality Standards are being met, identify and attempt to quantify pollutant concentrations emitted by industries, and identify sources that have the potential to release the highest amounts of pollutants. A majority of the air monitoring sites are currently being operated in or near the five largest cities and seven largest counties in the state. However, as EPA continues to lower the National Ambient Air Quality Standards, the department has established some of the monitoring sites in rural areas such as the Wind Cave National Park, Badlands National Park, Union County, and Pierre. These sites are helping to determine long range impacts from other states and countries on South Dakota's rural and urban areas.

5.2 Real Time Data

Air monitoring goals have shifted to the collection of data using continuous air monitoring samplers and providing the data as quickly as possible for the public to use. Continuous samplers provide more data at lower operational cost, which is necessary as EPA continues to expand ambient air monitoring programs for the same amount of funding or less. In many cases, the continuous monitoring can be accessed by phone and uploaded to a website for public use. The public can then use this data to determine if they need to take extra precautions when doing outdoor activities. The real time information is also used to monitor PM₁₀ and PM_{2.5} concentrations when high wind dust alerts are forecasted for Rapid City and all parameters during national or international events such as wildfires that impact South Dakota.

The sites reporting data to the department's real time webpage in 2019 were Wind Cave National Park, Badlands National Park, Brookings (Research Farm), Union County (Union County #1), Rapid City (Rapid City Credit Union and Black Hawk), Watertown, Pierre, and Sioux Falls (SD School) sites. The data includes hourly concentrations of PM₁₀, PM_{2.5}, Sulfur Dioxide, Nitrogen Dioxide, Carbon Monoxide, and ozone. South Dakota's air quality real time website is located at: <http://denr.sd.gov/des/aq/aarealtime.aspx>

In 2019, data uploaded from the PM_{2.5} and PM₁₀ monitors and ozone analyzers at Wind Cave National Park, Badlands National Park, Brookings Research Farm, Union County #1, Credit Union, Black Hawk, Watertown, Pierre, and SD School sites were reporting hourly data to EPA's AirNow website located at: <https://www.airnow.gov/>

This data along with other monitoring sites around the nation provides the public and EPA with near real time data to show current air pollution levels and forecast levels for long range transport. The goal for the future is to add other locations in the state to this website and to the department's website as funding becomes available.

5.3 Class I Areas

With the development of coal bed methane and oil and gas production in North Dakota, Wyoming, Montana and Colorado there is still a need for data in rural and small cities in the western part of the state. In addition, South Dakota has developed a plan to implement the regional haze regulations required by the federal Clean Air Act. The implementation of these regulations will put more importance on air pollution levels in the state's two class I areas of Badlands and Wind Cave National Parks.

Ambient air monitors were placed in these areas in order to determine background levels and the impact of long-range transport of air pollutants like particulate matter and ozone. In addition, continuous data is needed for modeling purposes to help in determining air quality permit requirements. The National Park sites collect data from Interagency Monitoring of Protected Visual Environments monitors for PM₁₀, PM_{2.5}, and chemical analysis of the collected particulates. The department collects PM₁₀, PM_{2.5}, Sulfur Dioxide, Nitrogen Dioxide, and ozone data at the Badlands Site and PM₁₀, PM_{2.5}, and ozone data at the Wind Cave Site.

5.4 Metropolitan Statistical Areas

Title 40 of the Code of Federal Regulations Part 58, Appendix D, contains information used to design an ambient air monitoring network and lists three basic objectives in designing an ambient air monitoring network. The three basic objectives are listed below:

1. Provide air pollution data to the general public in a timely manner. The department accomplishes this objective by providing near real time data on the department's website at: <http://denr.sd.gov/des/aq/aarealtime.aspx>

The sites reporting data to the department's real time webpage in 2019 were Wind Cave National Park, Badlands National Park, Brookings (Research Farm), Union County (Union County #1), Rapid City (Credit Union and Black Hawk sites), Watertown, Pierre (Airport), and Sioux Falls (SD School) sites. Specifically, in the Rapid City area, High Wind Dust Alerts are called when meteorological conditions are forecasted that could cause high PM₁₀ concentrations. This information along with a report graphing hourly concentrations recorded during the alert is also provided to the public through the department's website;

2. Support compliance with ambient air quality standards and emissions strategy development. The department accomplishes this objective by locating the sites throughout the state to assess the permit control measures and pollution emission impacts on the state. For example, the Rapid City air monitoring sites specifically evaluate the permit control measures and the special measures taken to reduce fugitive dust levels; and
3. Support for air pollution research studies. The department supports research by loading the air quality data into EPA's Air Quality System database site and by supporting local studies when funding is available.

EPA identified in Appendix D the minimum number of air monitoring SLAM sites and requirements for ozone, Carbon Monoxide, Nitrogen Dioxide, Sulfur Dioxide, particulate matter, and lead.

5.4.1 Required Ozone Monitoring Sites

The minimum number of required air monitoring sites for ozone is based on the population within a Metropolitan Statistical Area (MSA). There are three Metropolitan Statistical Areas in South Dakota. The Sioux Falls Metropolitan Statistical Area consists of Lincoln, McCook, Minnehaha, and Turner counties. The Rapid City Metropolitan Statistical Area consists of Custer, Meade and Pennington counties. Union County in South Dakota is part of the Sioux City Metropolitan Statistical Area which includes Dixon and Dakota counties in Nebraska and Woodbury and Plymouth County in Iowa.

To determine the number of monitoring sites for ozone, the design value is calculated, divided by the standard, and the results multiplied by 100. If the Metropolitan Statistical Area has a design value greater than 85% of the standard one site is required. The required number of sampling sites continues to increase as the population increases. If the highest concentration site in a Metropolitan Statistical Area has a design value less than 85% for ozone, the required number of sites may be one or even zero depending on the design value and population of the Metropolitan Statistical Area.

The typical peak ozone concentrations are expressed in the percentage of the design value (see Table 9-4) of the National Ambient Air Quality Standard for ozone (0.070 parts per million). Table 5-3 shows the population, design values as percent of the National Ambient Air Quality Standards and the minimum number of ozone monitoring site required for the Sioux Falls, Rapid City, and Sioux City Metropolitan Statistical Areas in the state after adding the data for the 2019 sampling year.

Table 5-3 – Minimum Ozone Sites Required

2019 MSA est Population	Counties	Sites	AQS ID	Design Values as % of the NAAQS	> 85% Criteria (Yes or No)	Minimum Sites Required
Sioux Falls MSA						
268,232	Minnehaha Lincoln McCook Turner	SD School	46-099-0008	Ozone 8-hr = 94%	Yes	1
Rapid City MSA						
142,107	Pennington Meade Custer	Black Hawk	46-093-0001	Ozone 8-hr = 69%	No	0
		Wind Cave	46-033-0132	Ozone 8-hr = 87%	Yes	1

2019 MSA est Population	Counties	Sites	AQS ID	Design Values as % of the NAAQS	> 85% Criteria (Yes or No)	Minimum Sites Required
Sioux City MSA						
144,701	Union, SD Dixon, NE Dakota, NE Woodbury, IA Plymouth, IA	UC #1	46-129-0003	Ozone 8-hr = 94%	Yes	1

There are two additional ambient air monitoring requirements in Appendix D for an ozone network. If a Metropolitan Statistical Area is required to have one or more ozone monitors, at least one of the ozone monitoring sites is required to be located at the expected high concentration area for the Metropolitan Statistical Area. The Metropolitan Statistical Areas in South Dakota do not require more than one ozone monitoring site, but the department does locate the ozone monitoring site at the expected high concentration in the area. Ozone monitoring at a SLAMS monitoring site is only required during the ozone season which is the months of March through October in South Dakota. The department operates the ozone monitors all year round because the department has determined through experience that the monitors have less operational problems when operated continuously.

As a result of evaluating the air monitoring site data, based on the design values and populations, South Dakota is required to have an ozone monitoring site in the Sioux Falls, Rapid City, and Sioux City Metropolitan Statistical Areas. Although Union County only represents a small percentage of the population of the Sioux City Metropolitan Statistical Area, the department is still required to operate one ozone monitoring site in Union County.

5.4.2 Required PM₁₀ Monitoring Sites

The minimum number of PM₁₀ monitoring sites is based on the population of the Metropolitan Statistical Area and the PM₁₀ concentrations within the Metropolitan Statistical Area. The Rapid City and Sioux City Metropolitan Statistical Areas in South Dakota have a population between 100,000 to 250,000 and the Sioux Falls Metropolitan Statistical Area has a population between 250,000 and 500,000. To determine the number of monitoring sites for PM₁₀, the maximum 24-hour concentration level at a site is divided by the standard (150 micrograms per cubic meter) and the results multiplied by 100. For the size of the Rapid City and Sioux City MSAs, if the percentage is over 120% of the standard, 1-2 sites are required; if the percentage is between 80% and 120% of the standard, 0-1 sites are required; and if the percentage is less than 80%, zero sites are required. For the size of the Sioux Falls MSA, if the percentage is over 120% of the standard, 3-4 sites are required; if the percentage is between 80% and 120% of the standard, 1-2 sites are required; and if the percentage is less than 80%, 0-1 sites are required.

Table 5-4 shows the population, the 24-hour maximum concentration as a percentage of the National Ambient Air Quality Standards, and the minimum site requirements for the Sioux Falls, Rapid City, and Sioux City Metropolitan Statistical Areas in the state.

Table 5-4 – Minimum PM₁₀ Sites Required

2019 MSA est Population	Counties	Site	AQS ID	PM ₁₀ Max Concentration as % of the NAAQS	> 80% Criteria (Yes or No)	Minimum Sites Required
Sioux Falls MSA						
268,232	Minnehaha Lincoln McCook Turner	SD School	46-099-0008	(38/150) (100) 24-hour = 25%	No	0 - 1
Rapid City MSA						
142,107	Pennington Meade Custer	RC Credit Union	46-103-0020	(185/150) (100) 24-hr = 123%	Yes	1 - 2
		RC Library	46-103-1001	(69/150) (100) 24-hr = 46%	No	0
		Black Hawk	46-093-0001	(57/150) (100) 24-hr = 38%	No	0
		Wind Cave	46-033-0132	(31/150) (100) 24-hr = 21%	No	0
Sioux City MSA						
142,107	Union, SD Dixon, NE Dakota, NE Woodbury, IA Plymouth, IA	UC #1	46-129-0001	(56/150) (100) 24-hr = 37%	No	0

5.4.3 Required PM_{2.5} Monitoring Sites

The minimum number of required air monitoring sites for PM_{2.5} is based on the population within a Metropolitan Statistical Area. As discussed for ozone monitoring sites, there are three Metropolitan Statistical Areas (Sioux Falls, Sioux City, and Rapid City) in South Dakota. All three Metropolitan Statistical Areas have a population from 50,000 to less than 500,000. In addition, each state must monitor for PM_{2.5} at their NCore site.

If the Metropolitan Statistical Area has a design value (see Tables 9-2 and 9-3) greater than 85% of the PM_{2.5} standards and the population is from 50,000 to less than 500,000 people, a minimum of one site is required. If the highest concentration site in a Metropolitan Statistical Area has a design value less than 85%, the minimum required number of sites for the above population range is zero.

Table 5-5 provides the data used to determine the minimum number of PM_{2.5} monitoring sites in each Metropolitan Statistical Area. As a result of evaluating the air monitoring site data, based on the design values and populations, South Dakota is not required to have a monitoring site, but still needs one at the NCore site. The department will still operate PM_{2.5} monitors in the Rapid

City MSA and Sioux City MSA to monitor impacts from local, national, and international events.

Table 5-5 – Minimum PM_{2.5} Sites Required

2019 MSA Population	Counties	Site	AQS ID	PM _{2.5} Design Values as % of the NAAQS	> 85% Criteria (Yes or No)	Minimum Sites Required
Sioux Falls MSA						
	Minnehaha Lincoln McCook Turner	SD School	46-099-0008	24-hour = 43%	No	0
		SD School	46-099-0008	Annual = 42%	No	0
Rapid City MSA						
	Pennington Meade Custer	RC Credit Union	46-103-0020	24-hr = 63%	No	0
		RC Credit Union	46-103-0020	Annual = 56%	No	0
		RC Library	46-103-1001	24-hr = 51%	No	0
		RC Library	46-103-1001	Annual = 47%	No	0
		Wind Cave	46-033-0132	24-hr = 40%	No	0
		Wind Cave	46-033-0132	Annual = 32%	No	0
Sioux City MSA						
	Union, SD Dixon, NE Dakota, NE Woodbury, IA	UC #1	46-129-0001	24-hr = 46%	No	0
		UC #1	46-129-0001	Annual = 52%	No	0

5.4.4 Required Carbon Monoxide Monitoring Sites

The minimum monitoring requirement for Carbon Monoxide is based on core-based statistical areas (CBSA) which are established by the Office of Management and Budget. Core-based statistical areas are Metropolitan Statistical Areas (i.e., 50,000 or more populations).

A minimum of one Carbon Monoxide monitor is required to operate collocated with one required near-road Nitrogen Dioxide monitor in core-based statistical areas with a population greater 1,000,000 or more persons. None of the core-based statistical areas in South Dakota meet the population criteria. Therefore, no Carbon Monoxide monitoring is required under the minimum requirements, but Carbon Monoxide must be measured at the state's NCore site.

5.4.5 Required Nitrogen Dioxide Monitoring Sites

A minimum of one Nitrogen Dioxide monitor is required to operate at a microscale near-road monitoring station and at an expected highest Nitrogen Dioxide concentration representing the neighborhood or larger spatial scales in a core based statistical area with a population level of 1,000,000 or greater. None of the core-based statistical areas in South Dakota meet the population criteria. Therefore, no Nitrogen Dioxide monitoring is required under the minimum requirements, but Nitrogen Dioxide must be measured at the state's NCore site.

5.4.6 Required Sulfur Dioxide Monitoring Sites

Sulfur dioxide has a population-based monitoring requirement for a core-based statistical area (CBSA). The monitoring requirement is based on multiplying the total amount of sulfur dioxide, in tons per year, emitted within the counties in the core-based statistical area by the population within the core-based statistical area. The resulting product is divided by one million, providing the population weighted emissions index (PWEI) for the core-based statistical area.

A micropolitan statistical area is defined as a core-based statistical area with a population of greater than 10,000 but less than 50,000 people. A core-based statistical area with a population of 50,000 people or greater is defined as a metropolitan statistical area. In accordance with 40 CFR Part 58, Appendix D, Section 4.4.2, the state must operate a minimum number of sulfur dioxide monitoring sites, as described below:

- For any core-based statistical area with a calculated PWEI value equal to or greater than 1,000,000, a minimum of three SO₂ monitors are required within that CBSA;
- For any CBSA with a calculated PWEI value equal to or greater than 100,000, but less than 1,000,000, a minimum of two SO₂ monitors are required within that CBSA; and
- For any CBSA with a calculated PWEI value equal to or greater than 5,000, but less than 100,000, a minimum of one SO₂ monitor is required within that CBSA.

Table 5-6 provides the data used for calculating the population weighted emissions index (PWEI) for each core-based statistical area (CBSA) and Micropolitan area in South Dakota. The Sulfur Dioxide emissions were derived from EPA's 2017 National Emission Inventory. None of the PWEI values calculated are greater than 5,000. Therefore, no sulfur dioxide monitoring is required under the minimum requirements. However, in accordance with 40 CFR Part 58, Appendix D, Section 3(b), sulfur dioxide must be measured at the state's NCore site.

Table 5-6 – Population Weighted Emission Index

CBSA	Est 2019 Population	Counties	SO₂ Emissions	PWEI
<i>Metropolitan Areas</i>				
Sioux Falls	268,232	Lincoln, McCook, Minnehaha, and Turner	632 tons per year	170
Sioux City	144,701	Union (SD), Dakota and Dixon (NE), and Woodbury and Plymouth (IA)	9,533 tons per year	1,379
Rapid City	142,107	Custer, Meade and Pennington	621 tons per year	88
<i>Micropolitan Areas</i>				
Aberdeen	43,191	Brown and Edmunds	137 tons per year	6
Brookings	35,232	Brookings	161 tons per year	6
Huron	18,883	Beadle	66 tons per year	1
Mitchell	23,166	Davison and Hanson	77 tons per year	2
Pierre	22,064	Hughes, Stanley and Sully	32 tons per year	1
Spearfish	25,741	Lawrence	188 tons per year	5
Vermillion	14,041	Clay	14 tons per year	0
Watertown	34,126	Codington and Hamlin	129 tons per year	4
Yankton	22,869	Yankton	81 tons per year	2

5.4.7 Required Lead Monitoring Sites

In 2010, EPA completed a rule change that required source type testing in addition to network testing. The rule originally required lead testing at the National Core Site. The final rule required lead testing at the National Core Site only if the site is in a city with a 500,000 and greater population. The National Core site is in Sioux Falls and the city has a population under 500,000 so no testing is required.

The department is also required to conduct ambient lead monitoring near lead sources which are expected to or have been shown to contribute to a maximum lead concentration in the ambient air in excess of the National Ambient Air Quality Standards. South Dakota is in attainment of the National Ambient Air Quality Standard for lead. At a minimum, there must be one source-orientated monitoring site located to measure the maximum lead concentration in the ambient air resulting from each non-airport lead source which emits 0.50 or more tons per year and from each airport which emits 1.0 or more tons per year based on the most recent National Emission Inventory or other scientifically justifiable methods and data. Based on EPA's 2017 National Emission Inventory, there are no sources that emit 0.50 or more tons per year and no airports that emit 1.0 or more tons per year. Therefore, lead monitoring is not required in South Dakota.

5.5 Additional Monitoring

The department operates the following additional types of monitors to meet the specific network requirements in 40 Code of Federal Regulations Part 58, Appendix D:

1. PM_{2.5} background and transport monitors at the Badlands and Wind Cave sites; and
2. National Core monitoring equipment located in the city of Sioux Falls at the SD School Site. Each State is required to operate at least one NCore site. The NCore sites must measure, at a minimum, PM_{2.5} particle mass using continuous and integrated/filter-based samplers, speciated PM_{2.5}, PM_{coarse} particle mass, ozone, Sulfur Dioxide, Carbon Monoxide, and Nitrogen Oxide/Total Reactive Nitrogen (NO/NO_y), wind speed, wind direction, relative humidity, and ambient temperature.

Another requirement in Appendix D is providing for a Photochemical Assessment Monitoring Stations (PAMS) which is required in areas classified as serious, severe, or extreme nonattainment for ozone. All areas in South Dakota are attaining the National Ambient Air Quality standard for ozone, so no Photochemical Assessment Monitoring Stations sites are required.

5.6 Future Monitoring

There is currently minimal monitoring being completed in other parts of the state that have small but expanding populations and industries. These areas include the northeastern and the northern Black Hills portions of the state. These areas will continue to be evaluated to determine whether additional monitoring efforts need to be conducted in those areas.

PM₁₀, PM_{2.5} and ozone will be the focus of the ambient air monitoring network as levels of these pollutants have the greatest potential to have concentrations close to the standard as EPA continues to lower the National Ambient Air Quality Standards for these pollutants.

6.0 NETWORK MODIFICATIONS FOR 2020

The department will continue to evaluate the air monitoring network in 2020 to determine if any new sites are needed and/or existing sites need to be modified or closed to meet the needs of South Dakota and or federal requirements.

6.1 New Sites

The department may need to move the air monitoring sites at the Sioux Falls SD School Site and the Rapid City Credit Union Site. The property owners have informed the department that the sites may need to be moved.

At the beginning of 2020, the department established a new monitoring site at the Aberdeen Bus Site to replace the Fire Station #1 Site. This allowed the department to install continuous PM₁₀

and PM_{2.5} monitors in Aberdeen in place of manual monitors. The Department will be able to add real time data for Aberdeen to the website and AirNow.

6.2 Sites Closed

As mentioned above, the Aberdeen Fire Station #1 Site was closed at the end of 2019.

The Library Site in Rapid City has operated since 1989 and is the oldest site in South Dakota. It was established to monitor the dust levels from fugitive sources such as sanding material placed on the roads during icy conditions. As the City of Rapid City changed from a limestone-based sanding material to a silica base and using liquid deicing material in the downtown area, the dust concentrations in the downtown area improved in the early 1990's. The Library Site was continued in the last few years because the City of Rapid City reduced the amount of liquid deicing material because it was impacting the water quality of Rapid Creek. The change did not impact dust levels in the downtown area. In fact, PM₁₀ concentrations at the Library Site continued to decline.

In 2019, the Library site had manual monitors for PM₁₀ and PM_{2.5}. The Credit Union site in Rapid City has PM₁₀ and PM_{2.5} continuous monitors. Of the two sites the Credit Union site experiences higher concentrations. The PM₁₀ concentrations at the Library site after reducing the amount of liquid deicing and increasing sanding materials continued to decline. Therefore, the department closed the Library Site in Rapid City at the end of 2019. Closing the Library Site will result in significant cost and time savings. In addition, it allows the department to use the savings and continue moving towards continuous monitoring and providing more real time data to the public.

6.3 Modifications

The department will continue to update older continuous style monitors with newer monitors. In 2020, the Department added an ozone analyzer at the Watertown site to expand transport observations farther North along the eastern border of the state.

7.0 REQUEST FOR WAIVER

There were no sampling frequency waivers requested for the 2019 sampling year.

8.0 EQUIPMENT REPLACEMENT PLAN

8.1 Overview

The department is tasked with sampling the ambient air quality throughout the state of South Dakota to demonstrate compliance with the National Ambient Air Quality Standards and to do special testing when needs arise or as required by EPA. In 2019, there were 11 active sites within South Dakota where criteria pollutants were monitored. The monitored pollutants include particulate matter (PM₁₀ and PM_{2.5}), Nitrogen Dioxide, Ozone, Carbon Monoxide, and Sulfur Dioxide.

The reliable operation of the monitors requires significant investment in staff time and inventory for upkeep, both which tend to increase as the monitors age. Monitors should be replaced when they reach an age when cost of upkeep meets or exceeds the cost of new purchase and when funding permits.

The operational life expectancy of a particulate matter monitor is about 10 years mainly due to detector and hardware board failures. With some major replacement of monitor components, the operational age may be extended.

Monitors also experience catastrophic failures, at which time a determination is made whether replacing core components on an aging instrument is viable. The age of some instruments makes sourcing parts difficult to impossible as they may no longer be supported by the manufacturer.

8.2 Data Loggers

In 2019, the department operated eight ESC 8832 style data loggers and one older style 8816 data logger. The nine data loggers were being used at each site that has continuous monitoring to provide near real time data to the public. Two additional previously used ESC 8832 data loggers were acquired in 2019 from another state agency, one of which is now being used at our new Aberdeen Bus Stop site, while the other is being kept in our laboratory to be used as a backup if needed. The department also has one extra older style 8816 data logger residing at the Badlands site that can be used as a backup if needed. The average age of the ESC 8816 and 8832 style data loggers is approximately 10 years. The department also has two newer style ESC 8872 style data loggers that are in the final stages of being made field ready. Table 8-1 provides the department's list of data loggers.

Table 8-1 - Data Logger Service Records

No.	Serial #	Model	Purchased	Comments
1	2506	8816	<2006	
2	4543	8816	<2006	Backup
3	2772	8832	2008	
4	2771K	8832	2008	
5	2770K	8832	2008	
6	2331K	8832	2008	
7	2431	8832	2008	
8	3992K	8832	2011	
9	4467K	8832	2012	
10	4868	8832	2015	
11	A3705K	8832	2019	ABN
12	A3119k	8832	2019	Backup
11	0622	8872	2016	Not field ready

No.	Serial #	Model	Purchased	Comments
12	0623	8872	2016	Not field ready

ESC discontinued the 8816 and 8832 models which makes it difficult to purchase replacement parts. Agilaire LLC, which purchased ESC, is offering various newer data logger versions, one of which is the PC-based 8872 model. The department purchased two ESC 8872 data loggers in federal fiscal year 2017. Shortly after purchasing the ESC 8872 data loggers, the department received reports from other states as well as from Agilaire that the computer-data logger interface is difficult to use. The department found this to be true since the department is still working on the two 8872 data loggers to prepare them for the field. After dedicating time and much effort to making them operational this past year, and after consulting with Agilaire and the State's IT department directly on multiple occasions, much progress was made. The last step is now to fix a slight error in programming code provided so that data from the 8872 can be transmitted to our AirVision server and software. Once they are programmed correctly, the department will deploy and field test one of the 8872 data loggers to determine if this data logger meets the department's needs or if another data logger needs to be evaluated.

The department is looking to purchase two more data loggers in federal fiscal years 2021 and 2022 if funding is available.

8.3 Manual Particulate Matter Monitors

8.3.1 Partisol Monitors

The department currently has eight Thermo Scientific Partisol 2000i manual monitors and four Thermo Scientific Partisol 2000 manual monitors (see Table 8-2). These Partisol manual monitors are Federal Reference Method (FRM) for PM_{2.5} and PM₁₀ monitoring. In 2019, eleven of the manual monitors were operating in the field.

Our oldest partisol monitors are now nine years old, with expected average longevity of 10-15 years. With the closing of the Aberdeen Fire Station site, and the Rapid City Library site at the end of 2019, only 2 partisol monitors will operate in the field in 2020. The department continues to experience a high rate of repair for the older models but does not plan to purchase any new manual monitors since two sites with manual monitor were closed. The department does have enough spare parts to keep the one remaining manual monitoring site at Sioux Falls operating.

Table 8-2 – Partisol Service Record

No.	Serial #	Model	Purchased	Comments
1	1041106	2000i	2011	
2	1031106	2000i	2011	
3	201021106	2000i	2011	
4	201011106	2000i	2011	
5	201881204	2000i	2011	

No.	Serial #	Model	Purchased	Comments
6	1751203	2000i	2012	
7	1891204	2000i	2012	
8	205631504	2000i	2016	
1	210881007	2000FRM	2010	
2	210851007	2000FRM	2010	
3	210771006	2000FRM	2010	
4	210801007	2000FRM	2010	

8.3.2 Hi-Vol PM₁₀ Monitors

The department currently does not operate any Hi-Vol Particulate Matter manual monitors. The department has chosen to retain four working monitors in case the need arises for lead monitoring, special studies, or for lab analysis to determine contribution from sources.

8.3.3 Speciation PM_{2.5} Monitors

The department currently does speciation monitoring at its National Core site. In 2009, the Met One SASS monitor was moved from the Hilltop site to the NCore site. In September 2009, the Interagency Monitoring of Protected Visual Environments URG 3000N sampler was set up to do the carbon sampling. In November 2016, EPA Region 8 gave the department a Met One Super SASS to replace the SASS. The SuperSASS allows two sample cartridges to be loaded enabling the sampler to collect samples every 3rd day with physical loading only required every 6th day.

8.4 Continuous Particulate Matter Monitors

The department operates two kinds of continuous PM monitors: 5014i BETA and a Met One BAM 1020. The typical lifespan for a continuous monitor running 24 hours a day, 365 days a year, is 10 years.

8.4.1 Thermo 5014i BETA Monitors

The department has two Thermo 5014i BETA continuous monitors listed in Table 8-3. These monitors are six years old. Each monitor has had substantial downtime due to hardware and software failures and hardware defects. Both monitors have been sent back to the manufacturer for repair on several occasions. Because of constant repairs, these monitors are no longer being used in the field, and serve as backups in the Pierre lab. The department will continue to use these monitors as a backup; however, replacement of this method should be considered when funding becomes available due to its unreliability.

Table 8-3 - 5014 Service Record

No.	Serial #	Purchased	Comments
1	CM13381007	2014	
2	CM13361013	2014	

8.4.2 Met One BAM 1020 Monitors

The department has 18 operating BAM continuous monitors and one in reserve (See Table 8-4). The oldest monitors are eleven years old. The department has not had many problems with these monitors but expect to begin having more operational problems as the monitors age. Because this monitor has been so reliable, the department has been gradually converting all continuous particulate monitoring to this method. Advantages to running one monitoring method are data consistency across sites, decreased training time for operators, reduced inventory of spare parts, and higher quality assurance during operational checks. The department purchased 3 BAM1020 monitors in 2019 in anticipation of opening a continuous Aberdeen site, and will investigate purchasing one more if additional funding is available.

Table 8-4 - BAM Service Record

No	Serial #	Purchased	Comments
1	H2949	2008	
2	H2972	2008	
3	H7027	2008	
4	H7028	2008	
5	H7051	2008	
6	H7236	2008	
7	K1801	2010	
8	M5333	2011	
9	M12165	2012	
10	T15065	2015	
11	T19274	2015	
12	T15079	2015	
13	U15820	2017	
14	U15821	2017	
15	W25139	2018	
16	X12895	2018	
17	Y14735	2019	Replaced BETA
18	Y21688	2019	ABN
19	Y14733	2019	CU

8.5 Continuous Gas Analyzers and Calibrators

The gaseous pollutant air monitoring network consists of continuous gas analyzers and calibrators that date back to 2003. The department has purchased various pieces of equipment nearly every year over the past decade. In 2019 the department purchased two new portable zero air supplies to be used for Performance Evaluations within the monitoring network. The department typically purchases replacement equipment for instruments that are 7–10 years old, although some analyzers, such as ozone can have a longer lifespan. During the fall of 2019, the

department repaired the aging Black Hawk shelter and is now using it as the continuous monitoring shelter in Aberdeen.

8.5.1 Ozone Analyzers

In 2019, the department operated ozone analyzers at six sites throughout South Dakota. An additional analyzer was added at the Watertown site during the first quarter of 2020. The ozone instruments have been some of the more reliable and durable instruments in the monitoring network.

The department purchased 2 new ozone analyzers in 2019, anticipating the needing to replace the ozone equipment at Brookings Research Farm and adding ozone at Watertown. This purchase gave us one backup ozone analyzer and one lab ozone analyzer. The lab ozone analyzer is used to conduct checks on ozone transfer standards and could be put in the field in case of an emergency (see Table 8-5). The department plans on purchasing another ozone analyzer in 2020 if funding is available.

Table 8-5 - Ozone Analyzers

No.	Serial #	Purchased	Comments
1	49c-78317-388	2003	
2	0414006406	2004	
3	0525812377	2005	
4	0615817056	2006	
5	0810029426	2008	
6	08270002	2008	Spare
7	1313057856	2013	Lab Analyzer
8	1427262856	2014	
9	SN1191893441	2019	BRK
10	SN1191893442	2019	WAT

8.5.2 Sulfur Dioxide Analyzers

The department operates Sulfur Dioxide analyzers at four sites in South Dakota. The department also has three Sulfur Dioxide backup analyzers for use when there is a major repair needed. There is one located in the lab in Pierre and one each at the Sioux Falls regional office and the Rapid City regional office.

The Sulfur Dioxide analyzers have been reliable and seldom need to be sent in for repair. Occasionally a lamp or detector needs to be replaced, which is something the department can do in-house. As with most Thermo Scientific instruments, the department does replace the pumps and installs pump kits on occasion, which is also something the department does in-house. The oldest model is from 2004 (see Table 8-6). The department originally planned to purchase a new Sulfur Dioxide analyzer in 2019, but other needs have pushed that purchase back to possibly 2020.

Table 8-6 - Sulfur Dioxide Analyzers

No.	Serial #	Purchased	Comments
1	0414006405	2004	Spare
2	0525112351	2005	
3	0621217058	2006	
4	0829531903	2008	Spare
5	0829531904	2008	Spare
6	0926837682	2009	
7	1117348531	2011	

8.5.3 Nitrogen Dioxide Analyzers

The department operates Nitrogen Dioxide analyzers at four sites in South Dakota. The National Core site in Sioux Falls also includes a NOy analyzer in addition to the traditional NOx analyzer. The department has three backup analyzers, which are typically housed at the regional offices in Sioux Falls and Rapid City.

Nitrogen Dioxide analyzers have been the most difficult to maintain and operate of the gaseous pollutant analyzers. Replacement parts can be very expensive and if the instrument needs to go back to the factory for repair, the cost can easily reach \$2,000 to \$3,000. The oldest Nitrogen Dioxide analyzers in our network were purchased in 2008 (see Table 8-7). During the last four months of 2019, the Credit Union site experienced several problems with the analyzers. The department was unable to purchase a new analyzer in 2019 but is hoping to purchase two new ones in 2020.

Table 8-7 - Nitrogen Dioxide Analyzers

No.	Serial #	Purchased	Comment
1	2411	2015	
2	3006	2016	
3	0824131747	2008	
4	298	2016	NOy
5	1116748523	2011	
6	1424162705	2014	Spare
7	0824131748	2008	Spare

8.5.4 Carbon Monoxide Analyzers

The department operates just one Carbon Monoxide analyzer at our National Core site in Sioux Falls. A Carbon Monoxide analyzer was located at Union County #1 for a few years but has since been moved to the National Core site in Sioux Falls. The Thermo Scientific Carbon Monoxide analyzer which was the main Carbon Monoxide at the National Core site is now the backup analyzer (see Table 8-8). The department is not planning to purchase a new Carbon Monoxide analyzer in 2020.

Table 8-8 - Carbon Monoxide Analyzers

No.	Serial #	Purchased	Comment
1	0723923521	2007	Spare
2	0174	2008	

8.5.5 Multi-gas/Ozone Calibrators

The department operates either a multi-gas or ozone calibrator at each of the monitoring sites with gas analyzers. There is also an Environics 6103 located at the Sioux Falls regional office and Rapid City regional office that are used by staff to conduct quarterly audits. The department originally used primarily Thermo Scientific calibrators for weekly checks and quarterly audits. Since then, the department started purchasing Environics 6103 calibrators, which can be used for multi-gas, ozone and photometer operation and are much lighter and easier to transport. Both types of calibrators have been very reliable and inexpensive to operate. The annual calibration of the flow controllers in these instruments has been the only recurring cost.

The department ordered two new ozone primary standards in 2019 to replace the two oldest models, which were purchased in 2003. These purchases were not originally planned but issues with the two oldest models pushed the timeline up to 2019 (see Table 8-9). The department may purchase another calibrator in federal fiscal year 2020, if funding is available.

Table 8-9 - Multi-gas/Ozone Calibrators

No.	Serial #	Model	Purchased	Comments
1	49CPS-7832-388	49CPS	2003	Spare
2	49CPS-78318-388	49CPS	2003	
3	0525812378	49i-PS	2005	Spare
4	0623018063	146i	2006	Spare
5	0824131746	49i-PS	2008	
6	0807328333	49i-PS	2008	
7	4290	6103	2008	
8	4298	6103	2008	
9	4299	6103	2008	
10	4561	6103	2009	
11	4562	6103	2009	

12	5047	6103	2011	
13	5881	6103	2013	
14	6223	6103	2014	
15	6588	6103	2015	

8.6 Meteorological Stations

The department currently has two meteorological (met) stations: Black Hawk and SD School sites. Each meteorological station consists of a temperature sensor, barometric pressure sensor, wind direction vane, and anemometer (wind speed) mounted on a 10-meter tower. The operation of each instrument on the tower is checked every month. The SD School meteorological station is audited once per quarter even though the audit requirements for a National Core Site is biannually. The Black Hawk met station is audited biannually even though it is only required annually.

The department's data needs at the other monitoring sites are being met by reliable and available data from the National Weather Service collected from nearby airports.

9.0 COMPLIANCE WITH NATIONAL AMBIENT AIR QUALITY STANDARDS

This section provides a comparison of the collected data to the National Ambient Air Quality Standards. The comparison will determine if an area is attaining the standard. In addition, the comparison will assist in determining if more monitoring stations for certain parameters are needed in an area or an area no longer needs to monitor for a certain parameter or parameters.

9.1 Particulate Matter (PM₁₀)

The PM₁₀ National Ambient Air Quality Standard is based on a 24-hour average concentration. The maximum 24-hour average concentration allowed is 150 micrograms per cubic meter. Attainment with the 24-hour standard is demonstrated when there is less than or equal to one expected exceedance per year averaged over three years. A 24-hour average concentration of 154.4 micrograms per cubic meter is the highest level that still attains the 24-hour standard for PM₁₀ based on EPA rounding to the nearest 10 micrograms per cubic meter.

In 2019, the statewide PM₁₀ monitoring network included 10 monitoring locations. Two of the sites recorded data using manual monitors providing 24-hour sample concentrations (i.e., Rapid City Library and Fire Station #1 (Aberdeen) sites). Eight of the sites used continuous samplers providing 1-hour concentrations at the Rapid City Credit Union, SD School (Sioux Falls), Watertown, Black Hawk Elementary, Brookings Research Farm, Badlands, Wind Cave, and UC #1 (Union County) sites. Badlands, Wind Cave, and UC #1 sites are rural sites.

Table 9-1 contains a list of the expected exceedance and attainment status for the PM₁₀ ambient air monitors throughout the state for calendar years 2017 to 2019.

Table 9-1 – Statewide PM₁₀ 24-Hour Concentrations

Site	Expected Exceedance	Attainment Status
Rapid City Library	0.0	Yes
Rapid City Credit Union	1.3	No *
Black Hawk Elementary	0.0	Yes
SD School	0.0	Yes
Badlands	0.0	Yes
Brookings Research Farm	0.0	Yes **
Fire Station #1	2.0	No ***
Watertown	0.0	Yes
Wind Cave	0.0	Yes
UC #1	0.0	Yes

* The expected exceedance level is the result of one fire event in 2017 and three high wind events in 2019 that were flagged in AQS.

**2019 data did not meet 75% completeness criteria.

***The expected exceedance level is the result of a dust storm event in 2018 that was flagged in AQS.

During 2017-2019, there were no PM₁₀ concentrations that exceeded the 24-hour standard at the Rapid City Library, Black Hawk Elementary, SD School, Badlands, Brookings Research Farm, Watertown, Wind Cave, or UC #1 sites.

At the Fire Station #1 site in Aberdeen, there was one exceedance in 2018. Since the manual monitor ran on a 1 in 6 day sampling schedule, this one exceedance caused the 3-year expected exceedance calculation of two. The exceedance was flagged as an exceptional event because it was caused by a dust storm which is considered a natural event. An exceptional event is an uncontrollable event caused by natural sources of particulate matter or an event that is not expected to recur at a given location.

According to the National Weather Service, “Leading up to the event, conditions were warm and generally dry in the James River Valley during May. Those conditions combined with strong winds from decaying thunderstorms in south central South Dakota to produce a dust storm. South winds of 50 to 80 mph kicked up a significant amount of dirt/dust as the winds moved north, leading to visibilities being reduced to below ¼ mile in many locations. The reduced visibilities caused a few traffic incidents and the winds knocked down trees, tree branches, and powerlines.” This was the first time the Fire Station #1 site experienced an exceedance in the 19 years it has operated. Therefore, the department believes this fits under the definition of an exceptional event and this exceedance was flagged in AQS. If needed, the department will develop an exceptional events package for this event and submit it to EPA for concurrence.

At the Rapid City Credit Union site, there was one fire event in 2017 and three high wind events in 2019 which resulted in an expected exceedance level of 1.3. These four events have been flagged in AQS and the department believes they fit under the definition of exceptional events. If needed, the department will develop an exceptional events package for these events and submit it to EPA for concurrence.

Title 40 of the Code of Federal Regulations Part 50.14 allows a State to exclude data showing exceedances or violations of any NAAQS that are directly due to an exceptional event from use in determinations. DENR has flagged the violation days in AQS and if needed will develop exceptional events packages for these events and submit them to EPA for concurrence. Therefore, the department considers all 10 sites in South Dakota to be demonstrating attainment of the PM₁₀ standard.

9.2 Particulate Matter (PM_{2.5})

The PM_{2.5} National Ambient Air Quality Standards consist of a 24-hour and an annual standard. The 24-hour standard is 35 micrograms per cubic meter. Attainment of the 24-hour standard is achieved when the maximum 24-hour average concentration, based on the annual 98th percentile averaged over three years (24-hour average design value), is less than or equal to 35 micrograms per cubic meter.

The PM_{2.5} annual standard is 12 micrograms per cubic meter. Attainment is demonstrated when the maximum annual arithmetic mean averaged over three consecutive years (annual design value) is equal to or less than 12 micrograms per cubic meter.

9.2.1 PM_{2.5} 24-Hour Standard

Table 9-2 shows the yearly 98th percentile for calendar years 2017 to 2019 used in the calculation of the 24-hour design value for PM_{2.5}, the 2019 24-hour design value, attainment status of each site, and the percent of the standard. The percent of the standard in this case and for the rest of the pollutants is the design value divided by the standard times 100.

In 2019, the highest 24-hour 98th percentile concentration was 18.3 micrograms per cubic meter and was recorded at the Aberdeen Fire Station #1 Site on a manual PM_{2.5} monitor. The site with the second highest 24-hour 98th percentile concentration in 2019 was at the Watertown Site with 17.5 micrograms per cubic meter collected on a continuous PM_{2.5} monitor.


Table 9-2 – Statewide PM_{2.5} 24-Hour Concentrations

Site	Yearly 98th Percentile	2019 24-hour Design Value	Attainment Status	Percent of the Standard
Rapid City Library	2017 – 19.2 ug/m ³ 2018 – 19.8 ug/m ³ 2019 – 14.9 ug/m ³	18 ug/m ³	Yes	51%
Rapid City Credit Union	2017 – 23.6 ug/m ³ 2018 – 26.5 ug/m ³ 2019 – 15.7 ug/m ³	22 ug/m ³	Yes	63%

Site	Yearly 98th Percentile	2019 24-hour Design Value	Attainment Status	Percent of the Standard
Badlands	2017 – 12.7 ug/m ³ 2018 – 18.5 ug/m ³ 2019 – 9.4 ug/m ³	14 ug/m ³	Yes	40%
Pierre Airport	2017 – 12.0 ug/m ³ 2018 – 13.5 ug/m ³ 2019 – 11.1 ug/m ³	12 ug/m ³	Yes	34%
SD School	2017 – 13.7 ug/m ³ 2018 – 15.7 ug/m ³ 2019 – 15.9 ug/m ³	15 ug/m ³	Yes	43%
Fire Station #1	2017 – 13.0 ug/m ³ 2018 – 22.3 ug/m ³ 2019 – 18.3 ug/m ³	18 ug/m ³	Yes	51%
Brookings Research Farm	2017 – 13.0 ug/m ³ 2018 – 12.1 ug/m ³ 2019 – 15.1 ug/m ³	13 ug/m ³	Yes	37%
Watertown	2017 – 17.0 ug/m ³ 2018 – 16.1 ug/m ³ 2019 – 17.5 ug/m ³	17 ug/m ³	Yes	49%
Wind Cave	2017 – 17.6 ug/m ³ 2018 – 15.9 ug/m ³ 2019 – 8.2 ug/m ³	14 ug/m ³	Yes	40%
UC #1	2017 – 14.5 ug/m ³ 2018 – 15.5 ug/m ³ 2019 – 16.5 ug/m ³	16 ug/m ³	Yes	46%

Figure 9-1 contains a graph of the 24-hour design values for each site. The highest design value for the 24-hour PM_{2.5} standard from 2017 to 2019 was recorded in Rapid City at the Credit Union site with a concentration of 22 micrograms per cubic meter. This represents 63% of the standard. The Pierre Airport site had the lowest 24-hour design values for PM_{2.5} at 12 micrograms per cubic meter or 34% of the standard. All sites are attaining the 24-hour PM_{2.5} standard.

Figure 9-1 – 2019 PM_{2.5} Statewide 24-Hour Design Values



9.2.2 PM_{2.5} Annual Standard

Table 9-3 contains a list of the annual averages, 2019 annual design values, attainment status, and percent of the standard for each of the PM_{2.5} sites using the data from 2017 to 2019 in the state. The highest annual average concentration in 2019 was recorded at the Watertown Site at 6.3 micrograms per cubic meter. The Wind Cave Site had the lowest annual average at 2.6 micrograms per cubic meter in 2019.


Table 9-3 – Statewide PM_{2.5} Annual Concentrations

Site	Annual Averages	2019 Annual Design Values	Attainment Status	Percent of the Standard
Watertown	2017 – 7.5 ug/m ³ 2018 – 7.7 ug/m ³ 2019 – 6.3 ug/m ³	7.2 ug/m ³	Yes	60%
Brookings Research Farm	2017 – 4.7 ug/m ³ 2018 – 4.7 ug/m ³ 2019 – 4.2 ug/m ³	4.5 ug/m ³	Yes	38%
SD School	2017 – 5.6 ug/m ³ 2018 – 5.5 ug/m ³ 2019 – 3.9 ug/m ³	5.0 ug/m ³	Yes	42%
UC #1	2017 – 6.4 ug/m ³ 2018 – 6.3 ug/m ³ 2019 – 5.8 ug/m ³	6.2 ug/m ³	Yes	52%
Fire Station #1	2017 – 5.8 ug/m ³ 2018 – 6.6 ug/m ³ 2019 – 5.9 ug/m ³	6.1 ug/m ³	Yes	51%

Site	Annual Averages	2019 Annual Design Values	Attainment Status	Percent of the Standard
Pierre Airport	2017 – 3.5 ug/m ³ 2018 – 4.1 ug/m ³ 2019 – 3.3 ug/m ³	3.6 ug/m ³	Yes	30%
Badlands	2017 – 3.6 ug/m ³ 2018 – 5.0 ug/m ³ 2019 – 3.7 ug/m ³	4.1 ug/m ³	Yes	34%
Wind Cave	2017 – 5.2 ug/m ³ 2018 – 3.6 ug/m ³ 2019 – 2.6 ug/m ³	3.8 ug/m ³	Yes	32%
Rapid City Library	2017 – 5.8 ug/m ³ 2018 – 6.1 ug/m ³ 2019 – 5.0 ug/m ³	5.6 ug/m ³	Yes	47%
Rapid City Credit Union	2017 – 7.6 ug/m ³ 2018 – 6.7 ug/m ³ 2019 – 5.9 ug/m ³	6.7 ug/m ³	Yes	56%

Figure 9-2 contains a graph of the PM_{2.5} annual average design value for each site. None of sites in the network had a 2019 design value that exceeded the annual PM_{2.5} standard. The highest annual design value occurred at the Watertown site with a level of 7.2 micrograms per cubic meter which is 60% of the annual standard. The lowest PM_{2.5} annual design value occurred at the Pierre Airport Site with a concentration of 3.6 micrograms per cubic meter which is 30% of the annual standard.

Figure 9-2 – 2019 PM_{2.5} Statewide Annual Design Values



9.3 Lead

During the early 1980's, the department conducted lead sampling. The levels detected were well below the National Ambient Air Quality Standards at that time. After passage of the 1990 Clean Air Act Amendments, there were concerns with the way EPA had instructed states in determining if those areas were in attainment of the lead standard. For this reason, a monitoring site was established in April 1992, at the Jaehn's Site in Rapid City to determine compliance with the standard. This site was downwind of GCC Dacotah, which is a cement plant that burns coal and has the potential to emit lead. The results of the analyzed data from the second quarter of 1992 through the first quarter of 1994 showed lead levels well below the National Ambient Air Quality Standards. Due to the low concentrations of lead in Rapid City, the sampling site was terminated at the end of the first quarter in 1994.

EPA changed the lead National Ambient Air Quality Standards on October 15, 2008. The change significantly lowered the lead standard from 1.5 micrograms per cubic meter to 0.15 micrograms per cubic meter based on the annual maximum three-month rolling average. Attainment of the lead National Ambient Air Quality Standards is achieved if the annual maximum three-month rolling average, averaged over a three-year period, is less than or equal to 0.15 micrograms per cubic meter.

The lead sampling in the past and current emissions levels indicates that South Dakota is attaining the new lead standard.

9.4 Ozone

Six ozone ambient air monitoring sites were operated in 2019. The analyzers were located at SD School, UC #1, Brookings Research Farm, Badlands, Black Hawk, and Wind Cave sites. The National Ambient Air Quality Standard for ozone consists of a daily 8-hour average of 0.070 parts per million. The 8-hour standard is met when the 3-year average of the annual fourth-highest daily maximum 8-hour average ozone concentration is less than or equal to 0.070 parts per million.

The 4th highest concentration for each year, 2019 8-hour design value in parts per million, attainment status, and percent of the standard for each of the sites can be seen in Table 9-4 and the 2019 design value is summarized in Figure 9-3. From 2017 to 2019, the Brookings Research Farm Site had the highest 3-year average ozone concentrations in the state at 0.067 parts per million, which is 96% of the ozone standard. The Black Hawk site is reporting the lowest ozone design value with 0.048 parts per million or 69% of the standard.

The SD School Site was the highest ozone concentration site in the state since 2010. In 2019, the Brookings Research Farm had the highest readings. There was a noticeable increase in concentrations since the beginning of the year and in the number of high concentrations at Brookings. EPA concurred these readings were out of the ordinary compared to the region. The department received a new ozone analyzer and put it at the Brookings site to do a side by side comparison toward the end of October. The two analyzers tracked very well, but the new analyzer read 6-7 ppb lower. On October 30, 2019, the new analyzer was put into service and


the Brookings's readings are more comparable to the other eastern sites. Before the beginning of the ozone season 2020, the department added an additional ozone analyzer in Watertown. This will expand our network along the entire eastern part of the state giving a better view of regional transport and another site to compare to the Brookings's readings.

The data collected in the past three years demonstrates that South Dakota is attaining the national ozone standard, but half of the sites are at least 90% of the ozone design value.

Table 9-4 – Statewide Ozone 4th highest Concentrations

Site	4th Highest Concentration	2019 8-Hour Design Values	Attainment Status	Percent of the Standard
SD School	2017 – 0.066 ppm 2018 – 0.069 ppm 2019 – 0.065 ppm	0.066 ppm	Yes	94%
Brookings Research Farm	2017 – 0.063 ppm 2018 – 0.067 ppm 2019 – 0.071 ppm	0.067 ppm	Yes	96%
Black Hawk	2017 – 0.045 ppm 2018 – 0.045 ppm 2019 – 0.055 ppm	0.048 ppm	Yes	69%
Badlands	2017 – 0.067 ppm 2018 – 0.063 ppm 2019 – 0.058 ppm	0.062 ppm	Yes	89%
Wind Cave	2017 – 0.065 ppm 2018 – 0.063 ppm 2019 – 0.057 ppm	0.061 ppm	Yes	87%
UC #1	2017 – 0.066 ppm 2018 – 0.068 ppm 2019 – 0.064 ppm	0.066 ppm	Yes	94%

Figure 9-3 – 2019 Ozone Design Values Statewide



9.5 Sulfur Dioxide

Four Sulfur Dioxide ambient air monitoring sites were operated in 2019. The analyzers were located at SD School, Badlands, Rapid City Credit Union, and UC #1 sites. The 1-hour Sulfur Dioxide standard concentration is 75 parts per billion. The area is attaining the standard when the three-year average of the yearly (99th percentile) of the daily maximum 1-hour average concentrations is less than or equal to 75 parts per billion (1-hour design value). The secondary Sulfur Dioxide standard is based on a 3-hour average concentration of 0.5 parts per million, not to be exceeded more than once per year.

9.5.1 Sulfur Dioxide 1-Hour Standard

Table 9-5 contains the yearly 99th percentile concentration, 1-hour design value, attainment status, and percent of the standard for each site. The Sulfur Dioxide 1-hour design values are based on Sulfur Dioxide data collected in 2017 to 2019. The highest 99th percentile 1-hour level in 2019 was recorded at the Badlands Site with 19 parts per billion.


Table 9-5 – 2019 Statewide Sulfur Dioxide 1-hour Design Values

Site	99 th Percentile Concentration	1-Hour Design Values	Attainment Status	Percent of the Standard
SD School	2017 – 5 ppb 2018 – 3 ppb 2019 – 2 ppb	3 ppb	Yes	4%
Rapid City Credit Union	2017 – 5 ppb 2018 – 2 ppb 2019 – 7 ppb	5 ppb	Yes	7%

Site	99 th Percentile Concentration	1-Hour Design Values	Attainment Status	Percent of the Standard
Badlands	2017 – 2 ppb 2018 – 1 ppb 2019 – 19 ppb	7 ppb	Yes	9%
UC #1	2017 – 4 ppb 2018 – 3 ppb 2019 – 3 ppb	3 ppb	Yes	4%

Figure 9-4 shows the three-year average of the yearly 99th percentile or design value for the 1-hour concentration for each of the sites in the network for 2019. All four of the sites recorded concentrations well under the 1-hour standard. The highest 1-hour design value was recorded at the Badlands Site with a concentration of 7 parts per billion which is 9% of the standard. The SD School and Union County sites each had concentrations of 3 parts per billion which is 4% of the standard. The data collected in the past three years demonstrates that South Dakota is attaining the 1-hour Sulfur Dioxide standard.

Figure 9-4 – 2019 Sulfur Dioxide 1-Hour Concentrations



9.5.2 Sulfur Dioxide 3-Hour Secondary Standard

The EPA Air Quality Systems does not calculate the yearly 3-hour average so a comparison could not be made to the secondary standard for Sulfur Dioxide. South Dakota has very low levels of Sulfur Dioxide at the four monitoring sites. Therefore, the department opted to use the maximum 1-hour concentrations as a comparison for the 3-hour standard for Sulfur Dioxide. The highest 1-hour average concentration was recorded at the Badlands site at 0.019 parts per million which is 4% of the Sulfur Dioxide secondary standard. Since the 1-hour average concentrations are not exceeding the secondary standard, all four sites are attaining the secondary standard for Sulfur Dioxide.

9.6 Nitrogen Dioxide

Beginning in 2010, the standard for Nitrogen Dioxide was revised by adding a 1-hour standard of 100 parts per billion and keeping the annual arithmetic mean standard of 53 parts per billion. Attainment is demonstrated when the 3-year average of 98th percentile daily maximum 1-hour concentration is less than or equal to 100 parts per billion (1-hour design value) and the annual arithmetic mean is less than or equal to 53 parts per billion (annual design value).

There were four Nitrogen Dioxide ambient air monitoring sites operated in 2019. The sampling locations were at the SD School, Badlands, Rapid City Credit Union, and UC #1 sites.

9.6.1 Nitrogen Dioxide 1-Hour Standard


Table 9-6 contains the 1-hour 98th percentile concentration for each of the last three years, 1-hour design values, attainment status, and percent of the standard for each site. The Rapid City Credit Union Site had the highest 2019 98th percentile 1-hour concentration at 33.8 parts per billion. The second highest 1-hour concentration for 2019 was recorded at the SD School Site at 31.2 parts per billion.

Table 9-6 – Nitrogen Dioxide 1-Hour 98th Percentile Concentrations

Site	98 th Percentile Concentration	1-Hour Design Values	Attainment Status	Percent of the Standard
SD School	2017 – 30.2 ppb 2018 – 34.1 ppb 2019 – 31.2 ppb	32 ppb	Yes	32%
Badlands	2017 – 3.8 ppb 2018 – 3.8 ppb 2019 – 8.0 ppb	5 ppb	Yes	5%
RC Credit Union	2017 – 39.9 ppb 2018 – 39.4 ppb 2019 – 33.8 ppb	38 ppb	Yes	38%
UC #1	2017 – 15.3 ppb 2018 – 17.7 ppb 2019 – 11.5 ppb	15 ppb	Yes	15%

Figure 9-5 shows the Nitrogen Dioxide 1-hour design values for each of the sites. The Rapid City Credit Union Site had the highest concentration at 38 parts per billion or 38% of the standard. The SD School Site recorded the 2nd highest 1-hour Nitrogen Dioxide design value at 32 parts per billion or 32% of the standard. All sites had concentrations under the 1-hour Nitrogen Dioxide standard and are attaining the standard using data from 2017 to 2019.


Figure 9-5 – Nitrogen Dioxide 1-hour Design Values 2019



9.6.2 Nitrogen Dioxide Annual Standard

Figure 9-6 shows the annual average for the four sites operated in 2019. The highest Nitrogen Dioxide annual average was recorded at the Rapid City Credit Union Site at 5.55 parts per billion. The Badlands Site remained near the detection level for the sampling method. In 2019, all four sites attained the annual standard for Nitrogen Dioxide.


Figure 9-6 – Nitrogen Dioxide Annual Concentration 2019



9.7 Carbon Monoxide


The Carbon Monoxide standard is based on two primary standards in the form of a one-hour and an 8-hour average concentration. The one-hour standard is 35.0 parts per million and is not to be exceeded more than once per year. The highest 1-hour concentration of Carbon Monoxide recorded in 2019 at the SD School Site was 1.3 parts per million. Figure 9-7 shows the Carbon Monoxide 1-hour maximum concentrations for the SD School Site from 2011 through 2019. The Carbon Monoxide concentrations are very low. The Carbon Monoxide data shows the area is attaining the 1-hour National Ambient Air Quality Standard.

Figure 9-7 - Carbon Monoxide 1-Hour Concentration 2019



The other standard is an 8-hour average concentration of 9.0 parts per million, not to be exceeded more than once per year. The highest 8-hour average recorded in 2019 at the SD School Site was 0.7 parts per million. Figure 9-8 shows the Carbon Monoxide maximum 8-hour average concentrations from the SD School Site from 2011 to 2019. The Carbon Monoxide concentrations are very low, and the area is attaining the 8-hour average National Ambient Air Quality Standard.

Figure 9-8 - Carbon Monoxide 8-Hour Average Concentration 2019



9.8 2019 High Concentrations Summary

Evaluating high concentration days are important because they affect the design values and need to be considered when evaluating the data results for each year. A conceptual theory on what caused the high concentrations can be formed and further developed in future years. In some cases, if local sources are causing the problem, early actions can be taken to reduce concentration levels and further protect public health from high levels. As EPA revises the national standards lower, information on the cause of the high concentration day needs to be collected soon after the event instead of three years after a standard revision. In some cases, the information may show long range transport or an exceptional event.

The department defined high concentration days as days where the concentration was 90% of or greater than the applicable standard. The evaluation of high concentration day for each parameter is as follows:

1. Ozone ≥ 0.063 parts per million, 8-hour average;
2. PM_{2.5} ≥ 32 micrograms per cubic meter, 24-hour average;
3. PM_{2.5} ≥ 10.8 ug/ m³, annual average;
4. PM₁₀ ≥ 135 ug/ m³, 24-hour average;
5. Nitrogen Dioxide ≥ 90.0 parts per billion, 1-hour maximum;
6. Sulfur Dioxide ≥ 67.0 parts per billion, 1-hour maximum;
7. Carbon Monoxide ≥ 8.1 parts per million, 8-hour average; and
8. Carbon Monoxide ≥ 31.5 parts per million 1-hour maximum.

A review of the data showed no high concentrations days at the following sites in 2019: Badlands, Aberdeen, Watertown, and Pierre. None of the recorded samples at any of the locations throughout the state for PM_{2.5} (annual), Sulfur Dioxide, Nitrogen Dioxide, and Carbon Monoxide (1-hour or 8-hour) had levels that exceeded the high concentration day criteria listed above for these pollutants.

9.8.1 PM_{2.5} High Concentration Days

In 2019, there was one high concentration day for the 24-hour PM_{2.5} standard throughout South Dakota. The high 24-hour PM_{2.5} readings were at the Rapid City Credit Union and Library sites on 2/8/19 and are shown in Table 9-7. The AirNow Air Quality Index (AQI) and AirNow Tech maps for the day are displayed in Appendix A. The AirNow Air Quality Index maps show the monitoring sites with high concentration days were at Moderate to Unhealthy for Sensitive Groups levels. The AirNow Tech maps show the wind barbs (direction and wind speed), fire locations, and the greyish areas represent smoke plumes. This high concentration day appears to be impacted by localized slash pile fires. The high concentration day did not cause a violation of the standard.

Table 9-7 – 2019 High 24-Hour PM_{2.5} Readings

No.	Site	Date	Monitor	Concentration (ug/m ³) ¹
1	RC Credit Union	2/8/19	Continuous	42
	RC Library		Manual	36

¹ – Bolded concentrations that are shaded represent PM_{2.5} concentrations that exceeded the 24-hour standard.

9.8.2 PM₁₀ High Concentration Days

During 2019, there were three high concentration days for PM₁₀ in South Dakota. The high concentration days all occurred at the Rapid City Credit Union Site and are shown in Table 9-8. The AirNow Air Quality Index (AQI) and AirNow Tech maps for each day are displayed in Appendix B.

At the Rapid City Credit Union site, all three high concentration days occurred when there were high winds. These three days have been flagged in AQS and the department believes they fit under the definition of exceptional events. If needed, the department will develop an exceptional events package for these events and submit it to EPA for its concurrence.

The department considers all 10 sites in South Dakota to be demonstrating attainment of the PM₁₀ 24-hour standard.

Table 9-8 - 2019 High 24-Hour PM₁₀ Readings

No.	Site	Date	Monitor	Concentration (ug/m ³) ¹
1	RC Credit Union	1/29/19	Continuous	170
2	RC Credit Union	2/14/19	Continuous	162
3	RC Credit Union	6/8/19	Continuous	185

¹ – Bolded concentrations that are shaded represent PM₁₀ concentrations that exceeded the 24-hour standard.

9.8.3 Ozone High Concentration Days

During 2019, there were 23 8-hour average high concentration days for ozone. As discussed earlier in 9.4, there was an increase of high readings at the Brookings Research Farm site. Of the five high readings at Sioux Falls and the four high readings at Union County, all but one occurred on a day that Brookings was also high. See Table 9-9 for the high readings.

Table 9-9 - 2019 High 8-Hour Average Ozone Readings

No.	Date	Monitor	Concentration (ppm) ¹
1	2/22/19	Brookings	0.064
2	2/23/19	Brookings	0.064
3	3/7/19	Brookings	0.064
4	3/10/19	Brookings	0.071
5	3/11/19	Brookings	0.069
6	3/16/19	Brookings	0.063
7	3/17/19	Brookings	0.065
8	3/18/19	Brookings	0.064
9	4/14/19	Brookings	0.065
10	4/25/19	Brookings	0.064
11	5/15/19	Brookings	0.065
		SD School	0.063
12	5/29/19	Wind Cave	0.065
		Black Hawk	0.064
13	5/30/19	Brookings	0.078
14	5/31/19	Brookings	0.065
15	6/3/19	Brookings	0.067
16	6/4/19	Wind Cave	0.063
17	6/5/19	UC #1	0.066
18	6/6/19	Brookings	0.072
		SD School	0.072
		UC #1	0.069
19	6/7/19	Brookings	0.072
		SD School	0.067
		UC #1	0.065
20	6/8/19	Brookings	0.067
		SD School	0.065
		UC #1	0.064
21	6/26/19	Brookings	0.067
		SD School	0.067
22	6/29/19	Brookings	0.071
23	9/17/19	Brookings	0.063

¹ – Bolded concentrations that are shaded represent ozone concentrations that exceeded the 8-hour average ozone standard.

The AirNow Air Quality Index (AQI) and AirNow Tech maps for each day are displayed in Appendix C. Of the 23 high concentration days, only five days exceeded the 8-hour average standard of 0.070 parts per million, with five at the Brookings site and one at the Sioux Falls site. The highest concentration occurred at the Brookings site with an 8-hour average of 0.078 parts per million on May 30, 2019 and may have been the result of Canadian fires. The second highest 8-hour average concentration was .072 parts per million on June 6, at Brookings and Sioux Falls and on June 7, at Sioux Falls. The occurrence of so many high concentrations at Brookings and not the other sites in eastern South Dakota may be a good indication that the analyzer may have been reading high.

In western South Dakota, high ozone concentrations occurred on two of the 23 days of high concentrations. The high concentrations occurred at Wind Cave and Black Hawk on May 29 and at Wind Cave on June 24.

In most cases, the AirNow Tech maps show local fires or smoke plumes from fires in other areas may have influenced the ozone concentrations in South Dakota. The 23 high concentrations days did not cause a violation of the 8-hour average ozone standard.

10.0 AIR MONITORING SITE TRENDS

This section will evaluate each air monitoring site in the network, determine if the site should be continued, and examine trends for each pollutant. Through this evaluation a determination is made if site goals are being met and if each testing parameter is needed at the site. This section also has site specific information tables including Air Quality System ID #, location, operation, data use, sampling schedule, monitoring objectives, spatial scale, and sampling and analytical methods required as part of the annual plan requirements in Title 40 of the Code of Federal Regulations Part 58.

10.1 Rapid City Area

The Rapid City area had a total of two monitoring sites collecting data in 2019. The high concentration site for PM₁₀ was located at the Rapid City Credit Union Site and a continuous PM₁₀ monitor was used to determine compliance with the National Ambient Air Quality Standards. In addition, Sulfur Dioxide, Nitrogen Dioxide, and PM_{2.5} analyzers were operated to determine current concentration levels. The Rapid City Library Site had manual Partisol 2000 and 2000i PM₁₀ and PM_{2.5} monitors collecting 24-hour data using a filter based gravimetric sampling method.

In cooperation with Rapid City, Pennington County, and local industry, the department is implementing a Natural Events Action Plan for the Rapid City area. Part of this plan is to alert the public of the potential of high dust levels caused by high winds and to advise the public of precautions to take during the high wind events. Under this plan high wind dust alerts are called by the National Weather Service when the following forecast conditions occur:

1. Hourly wind speeds exceed 20 miles per hour;
2. Peak wind gusts are greater than 40 miles per hour; and

3. Five consecutive days of 0.02 inches or less of precipitation each day excluding dry snow.

During 2019, one high wind dust alert was called for the Rapid City area on 1/7/19. This alert day did not exceed the PM₁₀ 24-hour standard. The Natural Events Action Plan for the Rapid City area is working to maintain PM₁₀ concentrations below the National Ambient Air Quality Standards during the high wind events on most days but still concentrations can exceed the standard.

An attainment designation was requested for PM₁₀ and was approved by EPA for the Rapid City area in 2006. An attainment designation for the 24-hour PM_{2.5} standard was requested for the Rapid City area in 2008 and for the annual PM_{2.5} standard in 2014. EPA designated Pennington and Meade Counties as attainment/unclassifiable for 24-hour standard in 2010 and the annual standard in 2015.

10.1.1 Rapid City Library Site

The Rapid City Library Site was located on the library building in Rapid City. The site was established in 1972, and it was the longest running sampling site in South Dakota. The site was geographically located in the downtown area of the city east of the hogback and in the Rapid Creek river valley. The site purpose was to evaluate population exposure, fugitive dust controls, the success of the street sanding and sweeping methods employed by the city of Rapid City and general concentration levels in the eastern part of the city. Figure 10-1 shows a picture of the Rapid City Library Site. The Library site had manual monitors for PM₁₀ and PM_{2.5}. The Credit Union site in Rapid City has PM₁₀ and PM_{2.5} continuous monitors. Of the two sites the Credit Union site experienced higher concentrations. The PM₁₀ concentrations at the Library site after reducing the amount of liquid deicing and increasing sanding materials continued to decline. Therefore, the department closed the Library Site in Rapid City at the end of 2019.

Figure 10-1 – Rapid City Library Site



PM₁₀ sampling began at the site in 1985. The PM₁₀ Hi-Vol monitors were replaced at the start of 2016 with low-volume manual Partisol 2000 monitors. The change in monitoring equipment standardized monitor flow rates between PM₁₀ and PM_{2.5} monitoring methods.

PM_{2.5} monitors were added to the site in 1999. In 2012, the Andersen RAAS 100 PM_{2.5} monitors were replaced with R&P Partisol 2000i monitors. Table 10-1 contains details on the monitoring site specific to the requirements in Title 40 of the Code of Federal Regulations Part 58.

Table 10-1 – Rapid City Library Site Specifics

Parameter	Information
Site Name	Rapid City Library
AQS ID Number	46-103-1001
Street Address	6 th and Quincy, Rapid City, South Dakota
Geographic Coordinates	UTM Zone 13, NAD 83, E 641,837.99, N 4,882,111.77
MSA	Rapid City
PM ₁₀	(Manual)
Sampler Type	Federal Reference Method RFPS-1298-126
Operating Schedule	Every 3 rd Day
Scale Representation	Neighborhood
Monitoring Objective	High Concentration and Population
Sampling Method	Partisol 2000
Analysis Methods	Gravimetric
Data Use	SLAMS (Comparison to the NAAQS),


Parameter	Information
PM_{2.5}	(Manual)
Sampler Type	Federal Equivalent Method RFPS-0498-117
Operating Schedule	Every 3 rd Day
Scale Representation	Neighborhood
Monitoring Objective	Population and High Concentration
Sampling Method	Partisol 2000i PM _{2.5} w/VSC Cyclone
Analysis Methods	Gravimetric
Data Use	SLAMS (Comparison to the NAAQS)

10.1.1.1 Rapid City Library Site PM₁₀ Data

Annual average PM₁₀ concentrations for the Rapid City Library Site are shown in Figure 10-2. The PM₁₀ concentrations show a trend of decreasing concentrations ranging from a high of 30 micrograms per cubic meter in 1991, to a low of 13 micrograms per cubic meter in 2019. The largest reduction in annual concentrations came when changes were implemented by the city on the street sanding and sweeping operations in the early 1990s. This was the only site east of the hogback in Rapid City and provided a check on fugitive and point source emissions for PM₁₀ in the eastern part of the city. In 2019, the Library site had manual monitors for PM₁₀ running on an every 3rd day sampling schedule.

The Credit Union site in Rapid City also has a PM₁₀ monitor. Of the two sites the Credit Union site shows the higher concentrations. The Library site was closed at the end of 2019.


Figure 10-2 – Rapid City Library Site PM₁₀ Annual Averages 2019



10.1.1.2 Rapid City Library Site PM_{2.5} Data

The graph in Figure 10-3 shows the PM_{2.5} annual average for each sampling year since 2001. The trend shows decreasing concentrations with the highest annual average at 7.8 micrograms per cubic meter in 2001 and the lowest at 4.9 micrograms per cubic meter in 2016. The concentration for 2019 was 5.0 micrograms per cubic meter. The annual average concentrations vary in difference from the highest to lowest annual average by 2.9 micrograms per cubic meter. The trends indicate a declining PM_{2.5} concentration levels for the site but for the past nine years the PM_{2.5} concentrations have leveled off. In 2019, the Library site had manual monitors for PM_{2.5} running on an every 3rd day sampling schedule. The Credit Union site in Rapid City also has a PM_{2.5} monitor. Of the two sites the Credit Union site shows the higher concentrations. The Library site was closed at the end of 2019.

Figure 10-3 – Rapid City Library Site PM_{2.5} Annual Averages 2019



10.1.2 Rapid City Credit Union Site

The Rapid City Credit Union Site is located on a lot next to Fire Station #3 building. The Rapid City Credit Union Site replaced the Fire Station #3 Site in October 2003 and is the high PM₁₀ concentration location for the western part of Rapid City. The Rapid City Credit Union Site is located just south of the quarry area and is centrally located in relation to the quarry facilities. Figure 10-4 contains a picture of the monitoring site looking in a northwest direction towards the quarry area. The goal of this site is to determine if the Rapid City area is attaining the PM₁₀, PM_{2.5}, Sulfur Dioxide, and Nitrogen Dioxide standards and population exposure. The department may need to move the Rapid City Credit Union Site. The department has been informed that this property may be sold and is unsure if the site can continue through the end of 2020.

Figure 10-4 – Rapid City Credit Union Site



Continuous Met One BAM PM₁₀ and PM_{2.5} particulate monitors and Thermo Sulfur Dioxide and Nitrogen Dioxide monitors were operated at this site in 2019. The continuous particulate matter monitors provide hourly concentrations on an everyday sampling schedule. The hourly readings from the continuous PM₁₀ monitor are used to investigate high concentration days for Rapid City and to compare concentrations to the PM₁₀ National Ambient Air Quality Standards. A continuous PM_{2.5} monitor is used to supply hourly data for investigation of high concentration days and to compare to the PM_{2.5} standards. In 2011, continuous Sulfur Dioxide and Nitrogen Dioxide analyzers were added to the Rapid City Credit Union Site to provide data on population exposure and source oriented testing near the facilities in the quarry area. Table 10-2 contains details on the monitoring site specific to the requirements in 40 Code of Federal Regulations Part 58.

Table 10-2 – Rapid City Credit Union Site Specifics

Parameter	Information
Site Name	Rapid City Credit Union
AQS ID Number	46-103-0020
Street Address	106 Kinney Ave.
Geographic Coordinates	UTM Zone 13, NAD 83, E 638,199.75, N 4,882,811.92
MSA	Rapid City
PM₁₀	(Continuous)
Sampler Type	Federal Equivalent Method EQPM-0798-122
Operating Schedule	Every Day
Scale Representation	Neighborhood
Monitoring Objective	High Concentration and Population
Sampling Method	Met One BAM-1020
Analysis Methods	Beta Attenuation
Data Use	SLAMS (Comparison to the NAAQS) and Real-Time Data


Parameter	Information
PM_{2.5}	(Continuous)
Sampler Type	Federal Equivalent Method EQPM-0308-170
Operating Schedule	Every Day
Scale Representation	Neighborhood
Monitoring Objective	Population and High Concentration
Sampling Method	Met One BAM-1020
Analysis Methods	Beta Attenuation
Data Use	SLAMS (Comparison to the NAAQS) Real-Time Data
SO₂	(Continuous)
Sampler Type	Federal Equivalent Method EQSA-0486-060
Operation Schedule	Every Day
Scale Representation	Neighborhood
Monitoring Objective	Population and High Concentration
Sampling Method	Instrumental Thermo 43i
Analysis Method	Pulsed Fluorescent
Data Use	SLAMS (Comparison to the NAAQS) and Real-Time Data
NO₂	(Continuous)
Sampler Type	Federal Reference Method RFNA-1289-074
Operation Schedule	Every Day
Scale Representation	Neighborhood
Monitoring Objective	Population and High Concentration
Sampling Method	Instrumental Thermo 42i
Analysis Method	Chemiluminescence
Data Use	SLAMS (Comparison to the NAAQS) and Real-Time Data

10.1.2.1 Rapid City Credit Union Site PM₁₀ Data

The Rapid City Credit Union Site began operation in October of 2003. Only three months of data was collected in 2003, so 2004 is the first complete sampling year. Figure 10-5 shows a graph of the annual average PM₁₀ concentration.

The PM₁₀ annual average concentration trend shows a declining level each year from 2004 to 2010. In 2011, average concentration levels increased back to the level in 2009 and increased through 2013. Since 2013, average concentration levels had declined until 2019. Testing for PM₁₀ concentrations is a priority for this site, since the Rapid City Library Site was closed at the end of 2019 and the parameter will be continued.

Figure 10-5 – Rapid City Credit Union Site PM₁₀ Annual Averages



10.1.2.2 Rapid City Credit Union Site PM_{2.5} Data


The testing for PM_{2.5} parameter using the manual method began at this site in October 2003 and completed the first full year of testing in 2004. The Rapid City Credit Union Site records the highest PM_{2.5} concentrations in the Rapid City area for both 24-hour and annual concentrations using the manual Federal Registered Method monitor.

In 2009, a continuous method PM_{2.5} monitor was added to the site as a special purpose monitor. Because the continuous monitor was a new method, EPA allowed the operation of the monitor as a special purpose method for up to three years before the data from the monitor is required to be compared to the PM_{2.5} standard. By the end of 2011, the continuous monitor had operated for three years and the Met One continuous PM_{2.5} monitor received the federal equivalent method number. Data was similar between the methods of PM_{2.5} monitoring, so as a cost savings measure the manual PM_{2.5} monitor was removed, and the continuous monitor became the state and local air monitoring stations monitor providing more valid data at a lower cost per year of operation.

Figure 10-6 shows the annual average for each sampling year since 2009 when the continuous monitor was setup. The annual average concentrations have varied through the years. In 2011, PM_{2.5} annual concentrations reached its lowest level with a concentration of 4.5 micrograms per cubic meter. The highest annual average for PM_{2.5} at this site was 9.5 micrograms per cubic meter in 2015. Smoke from wildfires in Canada and Pacific Northwest states had a large impact on the PM_{2.5} annual average concentration in 2015, 2017, and 2018.

The parameter of PM_{2.5} will be continued at this site using the continuous monitor to determine compliance with the National Ambient Air Quality Standards and to determine any change in concentration levels.

Figure 10-6 – Rapid City Credit Union Site PM_{2.5} Annual Averages




10.1.2.3 Rapid City Credit Union Site Sulfur Dioxide

Testing for Sulfur Dioxide started at the beginning of 2011 for this site. Some testing for the parameters was done in the 1990s but that data was old and there was need for the collection of new data. The annual standard for Sulfur Dioxide was dropped when the standard was revised so the 1-hour, daily maximum, 99 percentile concentrations will be used to track trends.

See Figure 10-7 for the 1-hour daily maximum concentration of Sulfur Dioxide recorded at the Rapid City Credit Union Site. The concentration level is low. Trends indicate a decreasing Sulfur Dioxide concentration level for this site. Testing for Sulfur Dioxide will continue at this site.

Figure 10-7 – Rapid City Credit Union Site Sulfur Dioxide 99th Percentile 1-hour Averages




10.1.2.4 Rapid City Credit Union Site Nitrogen Dioxide

Testing for Nitrogen Dioxide started at the beginning of 2011 for this site. Some testing for the parameter was completed in the 1990s but that data was old and there was a need for the collection of new data. The Nitrogen Dioxide standard includes a 1-hour and annual average concentration so the annual average will be represented to track trends.

See Figure 10-8 for concentrations of Nitrogen Dioxide at the Rapid City Credit Union Site. The concentrations are low. The trend line shows a slightly declining concentration level for the annual average. During the last third of 2019, the department experienced several problems with the analyzers, resulting in poor data completeness. Testing for Nitrogen Dioxide will continue at this site to further define the pollution level trend for this site.

Figure 10-8 – Rapid City Credit Union Site Nitrogen Dioxide Annual Averages



10.2 Black Hawk Site

Black Hawk is a small town located just north of Rapid City in Meade County north of the quarry area. Black Hawk is not an incorporated city but is a growing subdivision and is part of the Rapid City Metropolitan Statistical Area.

The Black Hawk Site was setup in the fall of 2000. The site is located on a small hill east of the Black Hawk Elementary School. PM_{10} and $PM_{2.5}$ monitors were located on a sampling shelter until October 2003 when the sampling shelter was moved to the Rapid City Credit Union Site. The monitors were then located on scaffolding within a fenced area until the fall of 2006 when a shelter was added back to the site. At the end of 2004, the $PM_{2.5}$ monitors were removed because concentrations were the lowest in the area and the potential for concentrations over the National Ambient Air Quality Standards were very low. In 2007, the ozone analyzer was moved from Rapid City Credit Union Site to the Black Hawk Site to determine ozone concentrations outside of the modeled one microgram Nitrogen Dioxide influence area from air quality sources in western Rapid City. See Figure 10-9 for a current picture of the site looking to the northwest.

The land use around the site is mainly residential with a few service type businesses. There are no obstructions around the monitoring site. The limestone quarry industries are located to the south and southeast of the Black Hawk Site and are expanding to ore bodies located closer to this site.

The current goal of the Black Hawk Site is to determine urban background concentrations for PM_{10} coming into the Rapid City area from the north and determine compliance with the ozone National Ambient Air Quality Standards in the Rapid City Metropolitan Statistical Area.

Figure 10-9 – Black Hawk Site



The site's spatial scale is neighborhood for PM₁₀ and ozone sampling. The objectives of the PM₁₀ sampling are high concentration, population, and source impact. The objectives of the ozone sampling are high concentration and population. The goals are being met. Table 10-3 contains details on the monitoring site specific to the requirements in Title 40 of the Code of Federal Regulations Part 58.

Table 10-3 – Black Hawk Site Specifics


Parameter	Information
Site Name	Black Hawk Elementary
AQS ID Number	46-093-0001
Street Address	7108 Seeaire Street
Geographic Coordinates	UTM Zone 13, NAD 83, E 634,683.07 N 4,890,309.65
MSA	Rapid City
PM₁₀	(Continuous)
Sampler Type	Federal Equivalent Method EQPM-1102-150
Operating Schedule	Every Day
Scale Representation	Neighborhood
Monitoring Objective	Population, Urban Background
Sampling Method	T A Series FH 62 C14 Continuous
Analysis Methods	Gravimetric
Data Use	SLAMS (Comparison to the NAAQS)

Parameter	Information
Ozone	(Continuous)
Sampler Type	Federal Equivalent Method EQOA-0880-047
Operating Schedule	Every Day
Scale Representation	Neighborhood
Monitoring Objective	Population and High Concentration
Sampling Method	Instrumental Thermo 49i
Analysis Methods	Ultraviolet
Data Use	SLAMS (Comparison to the NAAQS) and Real-time Data

10.2.1 Black Hawk Site PM₁₀ Data

Figure 10-10 contains a graph showing the PM₁₀ annual averages for the Black Hawk Site. The first three years of PM₁₀ concentration levels remained about the same. In 2004, the annual average dropped four micrograms per cubic meter. The highest annual average was 21 micrograms per cubic meter recorded in both 2001 and 2003. The lowest level of 10 micrograms per cubic meter was recorded in 2019. The overall trend shows a decrease in concentration. Plans are to continue to test for PM₁₀ at this location.


Figure 10-10 – Black Hawk Site – PM₁₀ Annual Averages



10.2.2 Black Hawk Site Ozone Data

The 2019 sampling year is the twelfth ozone season at the Black Hawk Site (see Figure 10-11). In the first year of testing (2008), the site recorded the second highest ozone level in the state. In 2012, the ozone levels were up statewide by 4 parts per billion and significantly at this site at 11 parts per billion. In 2019, ozone levels increased. The overall trends show a decrease in ozone concentration levels. Plans are to continue to test for ozone at this location.

Figure 10-11 – Black Hawk Site Ozone Yearly 4th Highest 8-hour Averages



10.3 Badlands Site

The Badlands National Park is one of two Class I areas in South Dakota designated for visibility protection under the Clean Air Act. The Badlands area is a large national park that attracts more than two million visitors each year. The Badlands area is a dry semi-desert area with short prairie grass and beautiful sandstone cliff vistas.

The Badlands Site was established in 2000, with manual monitors for particulate matter. Continuous monitors for particulate matter and gaseous air pollutants have been added over the years. Currently, the Badlands Site continuously monitors for PM₁₀, PM_{2.5}, Sulfur Dioxide, Nitrogen Dioxide, and ozone. The site is in the southeast part of the park near the visitor center. Figure 10-12 shows a current picture of the Badlands Site.

Figure 10-12 –Badlands Site



The Badlands Site is located next to the Interagency Monitoring of Protected Visual Environments site operated by the National Park Service. The Interagency Monitoring of Protected Visual Environments data is used to determine what types of sources are impacting the visibility of the national parks in South Dakota. The goal of having a state and local air monitoring station site next to the Interagency Monitoring of Protected Visual Environments site is to determine air pollution background levels and to see if pollution trends show long range transport of air pollution into the state. Table 10-4 contains details on the monitoring site specific to the requirements in Title 40 of the Code of Federal Regulations Part 58.

Table 10-4 – Badlands Site Specifics

Parameter	Information
Site Name	Badlands
AQS ID Number	46-071-0001
Street Address	25216 Ben Reifel Road, Interior, South Dakota 57750
Geographic Coordinates	UTM Zone 14, NAD 83, E 263,173.81 N 4,847,799.95
MSA	None
PM₁₀	(Continuous)
Sampler Type	Federal Equivalent Method EQPM-0798-122
Operating Schedule	Every Day
Scale Representation	Regional
Monitoring Objective	Background, Transport
Sampling Method	Met One BAM - 1020
Analysis Method	Beta Attenuation
Data Use	SLAMS (Comparison to the NAAQS) Real-time Data

Parameter	Information
PM_{2.5}	(Continuous)
Sampler Type	Federal Equivalent Method EQPM-0308-170
Operating Schedule	Every Day
Scale Representation	Regional
Monitoring Objective	Background, Transport
Sampling Method	Met One BAM-1020 w/PM _{2.5} VSCC
Analysis Method	Beta Attenuation
Data Use	Real-time Data and SLAMS (Comparison to the NAAQS)
SO₂	(Continuous)
Sampler Type	Federal Equivalent Method EQSA-0486-060
Operating Schedule	Every Day
Scale Representation	Regional
Monitoring Objective	Background, Transport
Sampling Method	Instrumental Thermo 43c
Analysis Methods	Pulsed Fluorescent
Data Use	SLAMS (Comparison to the NAAQS) Real-time Data
NO₂	(Continuous)
Sampler Type	Federal Reference Method RFNA-1289-074
Operating Schedule	Every Day
Scale Representation	Regional
Monitoring Objective	Background, Transport
Sampling Method	Instrumental Thermo 42i
Analysis Method	Chemiluminescence
Data Use	SLAMS (Comparison to the NAAQS) Real-time Data
Ozone	(Continuous)
Sampler Type	Federal Equivalent Method EQOA-0880-047
Operating Schedule	Every Day
Scale Representation	Regional
Monitoring Objective	Background, Transport
Sampling Method	Instrumental Thermo 49i
Analysis Method	Ultraviolet
Data Use	SLAMS (Comparison to the NAAQS) and Real-time Data


10.3.1 Badlands Site – PM₁₀ Data

PM₁₀ data has been collected at this site since 2000. The PM₁₀ manual monitors were operated on an every sixth day schedule from 2000 through 2004. As of 2005, continuous monitoring methods have been employed.

Figure 10-13 contains a graph of the annual averages for the Badlands Site since the continuous monitor was installed. The annual average concentration over the last 15 years varied only slightly overall. The highest annual average concentration of 12 micrograms per cubic meter was recorded in 2007. The lowest annual average concentration of 7 micrograms per cubic meter was recorded in 2009. The PM₁₀ concentrations recorded at this site are some of the

lowest levels in the state and represent background levels for the western half of the state. This parameter is meeting the goals for testing at this site and will be continued.

Figure 10-13 – Badlands Site – PM₁₀ Annual Averages




10.3.2 Badlands Site – PM_{2.5} Data

The PM_{2.5} manual monitors ran on an every third day schedule from 2001 to 2008. Beginning in 2009, the continuous Met One BAM-1020 Federal Equivalent Method replaced the manual RAAS 100 and the sampling schedule went to every day providing hourly and 24-hour average concentrations.

Figure 10-14 contains a graph of the annual averages for the continuous monitoring data. The annual averages for the Badlands Site show a concentration range with a high of 5.3 micrograms per cubic meter in 2013 and a low of 2.5 micrograms per cubic meter in 2016. Like the annual PM₁₀ concentrations, PM_{2.5} concentrations at this site have varied slightly over the years and are the lowest in the state. PM_{2.5} concentrations at the Badlands Site represent background levels for western South Dakota. This parameter is meeting the goals for testing at this site and will be continued.


Figure 10-14 – Badlands Site – PM_{2.5} Annual Averages



10.3.3 Badlands Site – Sulfur Dioxide Data

The first year of testing at the Badlands Site for Sulfur Dioxide occurred in 2005. As expected, concentrations for Sulfur Dioxide are very low. In 2019, the annual 99th percentile Sulfur Dioxide concentration was the highest recorded in the history of the site at 19.1 parts per billion. See Figure 10-15 to view a graph of the annual 99th percentile concentrations for Sulfur Dioxide. The linear trend line shows a slight increase in concentrations, but levels are very low and indicate minimal concentrations of Sulfur Dioxide. This parameter is meeting the goals for testing at this site and will be continued.

Figure 10-15 – Badlands Site – Sulfur Dioxide 99th Percentile 1-hour Average




10.3.4 Badlands Site Ozone Data

The first year of testing at the Badlands Site for ozone was in 2005, with equipment being operated by the National Park Service. The department completed quarterly audits of the ozone analyzer so data could be compared to the National Ambient Air Quality Standards. At the beginning of 2008 sampling year, the department took over the operation of the ozone analyzer.

Concentrations of ozone at this site have varied up and down over the fifteen years of testing. The yearly 4th highest 8-hour average ranged from a high of 0.071 parts per million in 2006 to a low of 0.052 parts per million in 2011. Currently it appears the ozone concentrations are on a slight decline. See Figure 10-16 to view a graph of the yearly 4th highest 8-hour average.

This parameter will continue to be a priority at this location because of past concentration levels at a site representing a rural area in western South Dakota and the testing is meeting the needs to continue the sampling effort.

Figure 10-16 – Badlands Site – Ozone Yearly 4th Highest 8-hour Averages




10.3.5 Badlands Site – Nitrogen Dioxide Data

The first year of testing at the Badlands Site for Nitrogen Dioxide occurred in 2005. As expected, concentrations for Nitrogen Dioxide are very low and represent background levels. Many hourly concentrations are at the detection limit of the analyzer at 1.0 part per billion. The calculated annual average levels for all fifteen years are close to the detection level for Nitrogen Dioxide.

See Figure 10-17 to view a graph of the annual average concentrations. The linear trends line shows a stable concentration level. This parameter will continue at this location providing background concentration levels for western South Dakota.

Figure 10-17 – Badlands Site – Nitrogen Dioxide Annual Averages



10.4 Wind Cave Site

The Wind Cave National Park is one of two Class I areas in South Dakota designated for visibility protection under the Clean Air Act. The Wind Cave area is a large national park located in the southern Black Hills of South Dakota.

The Wind Cave Site was established in 2005, with manual monitors for PM_{2.5} and continuous monitors for PM_{2.5}, PM₁₀, Sulfur Dioxide, Nitrogen Dioxide, and ozone. At the end of 2010, the manual PM_{2.5} monitors were removed from the site leaving only the continuous PM_{2.5} monitor for this parameter. Currently, the Wind Cave Site continuously monitors for PM₁₀, PM_{2.5}, and ozone. The site is located a short distance west of the visitor center. Figure 10-18 shows a current picture of the Wind Cave Site.

Figure 10-18 – Wind Cave Site



The monitoring equipment at the Wind Cave Site is in a sampling shelter next to the Interagency Monitoring of Protected Visual Environments site operated by the National Park Service. The Interagency Monitoring of Protected Visual Environments data will be used to determine what types of sources are impacting the visibility of the national parks in South Dakota. The purpose of having a State and Local Air Monitoring Stations site next to the Interagency Monitoring of Protected Visual Environments site is to determine air pollution background levels, and to see if pollution trends show long range transport of air pollution from outside of the state. Table 10-5 contains details on the monitoring site specific to the requirements in Title 40 of the Code of Federal Regulations Part 58.

Table 10-5 – Wind Cave Site Specifics

Parameter	Information
Site Name	Wind Cave
AQS ID Number	46-033-0132
Street Address	290 Elk Mountain Camp Road, Hot Springs, South Dakota
Geographic Coordinates	UTM Zone 13, NAD 83, E 622,471.56 N 4,823,856.93
MSA	Rapid City
PM₁₀	(Continuous)
Sampler Type	Federal Equivalent Method EQPM-0798-122
Operating Schedule	Every Day
Scale Representation	Regional
Monitoring Objective	Background, Transport
Sampling Method	Met One BAM - 1020
Analysis Method	Beta Attenuation
Data Use	SLAMS (Comparison to the NAAQS) Real-time Data


Parameter	Information
PM_{2.5}	(Continuous)
Sampler Type	Federal Equivalent Method EQPM-0308-170
Operating Schedule	Every Day
Scale Representation	Regional
Monitoring Objective	Background, Transport
Sampling Method	Met One BAM-1020 FEM
Analysis Method	Beta Attenuation
Data Use	Real-time Data and SPMs
Ozone	(Continuous)
Sampler Type	Federal Equivalent Method EQOA-0880-047
Operating Schedule	Every Day
Scale Representation	Regional
Monitoring Objective	Background, Transport
Sampling Method	Instrumental Thermo 49i
Analysis Method	Ultra Violet
Data Use	SLAMS (Comparison to the NAAQS) Real-time Data

10.4.1 Wind Cave Site PM₁₀ Data

The PM₁₀ concentrations at this site are one of the lowest in the state and are similar in concentrations as the Badlands Site. The Wind Cave Site is the most remote site in the state and a site that has no influence from industry and agriculture activities near the location. Figure 10-19 contains a graph showing the annual average PM₁₀ concentrations.

The 2019 PM₁₀ concentrations were the lowest they have been at the site. The trend line indicates steady concentration levels over the 15 years of testing. The concentrations ranged from 6 to 10 micrograms per cubic meter and are very low representing background levels in western South Dakota. This parameter is meeting the goals of background, visibility protection, long range transport, and will be continued.

Figure 10-19 - Wind Cave Site – PM₁₀ Annual Averages




10.4.2 Wind Cave Site PM_{2.5} Data

The PM_{2.5} concentrations are like the levels recorded at the Badlands Site and are some of the lowest in the state. Figure 10-20 contains a graph showing the annual average PM_{2.5} concentration levels.

The PM_{2.5} annual average concentrations range from 6.5 micrograms per cubic meter in 2009 to 1.9 micrograms per cubic meter in 2016. Concentrations were down in 2019 for this site. This parameter is meeting the goals of background, visibility protection, and long-range transport and will be continued.

Figure 10-20 - Wind Cave Site – PM_{2.5} Annual Averages




10.4.3 Wind Cave Site Ozone Data

Figure 10-21 contains a graph of the ozone 8-hour concentrations for the Wind Cave Site since 2005. The Wind Cave Site had the highest reported yearly 4th highest 8-hour ozone level in the state at 0.073 parts per million recorded in 2006. Ozone levels began to fall in 2007, in 2008 through 2011 the ozone concentrations leveled out. In 2012, Wind Cave ozone levels jumped back up to the approximate levels recorded when the department first started monitoring for ozone. However, in 2013 through 2016 the ozone concentrations dropped and leveled out similar to what occurred in 2008 through 2011. During 2017, there was an increase in concentration levels. During the past two years the levels have decreased. The overall trend at the site shows a decrease in concentration.

Testing for ozone is meeting the needs of the monitoring network by detecting transport pollution levels for this area of the state. Therefore, this parameter will be continued.

Figure 10-21 – Wind Cave Ozone Yearly 4th Highest 8-hour Averages



10.5 SD School Site - Sioux Falls Area

In 2019, one sampling site was operated in the Sioux Falls area, the SD School Site. The SD School Site replaced the SF Hilltop Site on January 1, 2008. The site is the National Core site for the state and monitors for PM₁₀, PM_{2.5}, ozone, Carbon Monoxide, Sulfur Dioxide, and Nitrogen Dioxide. In addition, special purpose parameters are sampled including PM_{coarse}, speciation PM_{2.5} and Total Reactive Nitrogen. This is a very busy monitoring site collecting more than 140,000 data points per year all loaded to the EPA national database. Figure 10-22 shows a current picture of the SD School Site.

Figure 10-22 – SD School Site



The SD School Site is located on the east central part of the city. The site is about 1.2 miles southeast of the main industrial area in Sioux Falls. The area around the site is mainly residential. Interstate 229 which is a major commuting road runs north and south about three city blocks east of the monitoring site. Table 10-6 contains details on the monitoring site specific to the requirements in Title 40 of the Code of Federal Regulations Part 58. In addition to the parameters listed in Table 10-6, a PM_{2.5} speciation monitor is operated at an every 3rd day sampling schedule. The department may need to move the Sioux Falls SD School Site. The department has been informed that the property has been sold and is unsure if this site can continue at this location through the end of 2020.

Table 10-6 – SD School Site Specifics

Parameter	Information
Site Name	SD School
AQS ID Number	46-099-0008
Street Address	2009 East 8 th Street, Sioux Falls, SD
Geographic Coordinates	UTM Zone 14, NAD 83, E 687,288.70 N 4,822,930.29
MSA	Sioux Falls


Parameter	Information
PM₁₀	(Continuous)
Sampler Type	Federal Equivalent Method EQPM-0798-122
Operating Schedule	Every Daily/Hourly
Scale Representation	Neighborhood
Monitoring Objective	Population and High Concentration
Sampling Method	Met One BAM-1020
Analysis Methods	beta attenuation
Data Use	SLAMS (Comparison to the NAAQS)
PM_{2.5}	(Manual)
Sampler Type	Federal Reference Method RFPS-0498-117
Operating Schedule	Every 3 rd Day
Scale Representation	Neighborhood
Monitoring Objective	Population and High Concentration
Sampling Method	Partisol 2000 w/VSCC
Analysis Methods	Gravimetric
Data Use	SLAMS (Comparison to the NAAQS)
PM_{10-2.5}	(Continuous)
Sampler Type	Federal Equivalent Method EQPM-0709-185
Operating Schedule	Every Daily/Hourly
Scale Representation	Neighborhood
Monitoring Objective	Population and High Concentration
Sampling Method	Met One BAM-1020
Analysis Methods	beta attenuation
Data Use	SLAMS (Comparison to the NAAQS)
PM_{2.5}	(Continuous)
Sampler Type	Federal Equivalent Method EQPM-0308-170
Operating Schedule	Every Daily/Hourly
Scale Representation	Neighborhood
Monitoring Objective	Population and High Concentration
Sampling Method	Met One BAM-1020
Analysis Methods	beta attenuation
Data Use	SLAMS (Comparison to the NAAQS)
Ozone	(Continuous)
Sampler Type	Federal Equivalent Method EQOA-0880-047
Operating Schedule	Hourly
Scale Representation	Neighborhood
Monitoring Objective	High Concentration and Population
Sampling Method	Instrumental Thermo 49C
Analysis Methods	Ultraviolet
Data Use	SLAMS (Comparison to the NAAQS), Real-time Data
NO₂	(Continuous)
Sampler Type	Federal Reference Method RFNA-1194-099
Operating Schedule	Hourly
Scale Representation	Neighborhood

Parameter	Information
Monitoring Objective	High Concentration and Population
Sampling Method	Teledyne API's T200
Analysis Methods	Chemiluminescence detection
Data Use	SLAMS (Comparison to the NAAQS), Real-time Data
NO_y	(Continuous)
Sampler Type	None
Operating Schedule	Hourly
Scale Representation	Neighborhood
Monitoring Objective	Population
Sampling Method	Teledyne API's T200
Analysis Methods	Chemiluminescence NO-Dif-NO _y
Data Use	SPMs
SO₂	(Continuous)
Sampler Type	Federal Equivalent Method EQSA-0486-060
Operating Schedule	Hourly
Scale Representation	Neighborhood
Monitoring Objective	High Concentration and Population
Sampling Method	Instrumental Thermo 43i TLE
Analysis Methods	Pulsed Fluorescence
Data Use	SLAMS (Comparison to the NAAQS), Real-time Data
CO	(Continuous)
Sampler Type	Federal Reference Method RFCA-1093-093
Operating Schedule	Hourly
Scale Representation	Neighborhood
Monitoring Objective	High Concentration and Population
Sampling Method	Teledyne API 300E
Analysis Methods	Gas/Filter/Correlation
Data Use	SLAMS (Comparison to the NAAQS), Real-time Data

10.5.1 SD School Site PM₁₀ Data

Figure 10-23 shows a graph of the PM₁₀ annual averages since 2008. The annual averages at the SD School Site range from a high of 22 micrograms per cubic meter in 2015 to a low of 12 micrograms per cubic meter in 2019. The trend line indicates a slightly decreasing concentration level. This parameter is meeting the goals of high concentration and population and will be continued.

Figure 10-23 – SD School Site – PM₁₀ Annual Averages




10.5.2 SD School Site – PM_{2.5} Data

PM_{2.5} data has been collected at this site since 2008. Annual averages for the SD School Site range from a low of 3.9 micrograms per cubic meter in 2018 to a high of 10.3 micrograms per cubic meter in 2010. The overall trend at this site shows a decrease in concentration levels with a continuous decline since 2015. Figure 10-24 contains a graph of the annual averages.

This parameter will remain a priority because of past high concentrations levels for the annual and 24-hour standards. Testing for this parameter is meeting the goals of high concentration and population and will be continued.

Figure 10-24 – SD School Site – PM_{2.5} Annual Averages




10.5.3 SD School Site Ozone Data

Sampling began for ozone at this site in 2008. The highest yearly 4th highest 8-hour ozone concentration recorded at this site was in 2012 at 0.072 parts per million. The lowest yearly 4th highest 8-hour ozone concentration was recorded at 0.061 parts per million in 2008 and 2015. The trend line shows a slightly increasing level of ozone over the 12 years of testing. In 2019, concentrations of ozone were slightly less than the past three years. Figure 10-25 contains a graph of each year's 4th highest ozone concentration level.

This parameter is meeting the goals of high concentration and population testing and is one of the highest sites in the state so the testing will be continued at this site.

Figure 10-25 – SD School Site - Ozone Yearly 4th Highest 8-Hour Averages




10.5.4 SD School Site Sulfur Dioxide Data

Testing for Sulfur Dioxide started in 2008 at this site. The levels of Sulfur Dioxide have dropped in concentration since the first year of testing. The type of analyzer was changed to a trace level Sulfur Dioxide analyzer in 2011. The detection level of this analyzer is now 0.1 parts per billion.

Sulfur Dioxide concentrations leveled out in 2010 through 2013 with the 1-hour 99th percentile for each year ranging from 3.3 to 5.5 parts per billion. In 2014, the 1-hour 99th percentile for Sulfur Dioxide concentrations jumped up to 10.3 parts per billion. Since then the concentrations of Sulfur Dioxide have decreased, with 2019 having the lowest level recorded at 2.3 parts per billion. The trend line shows a decline in concentrations of Sulfur Dioxide over the 12 years of testing. Figure 10-26 contains a graph of the Sulfur Dioxide yearly 1-hour 99th percentile for each sampling year. This parameter is meeting the goals of high concentration and population and testing will be continued at this site.


Figure 10-26 – SD School Site – Sulfur Dioxide Yearly 1-hour 99th Percentile



10.5.5 SD School Site Nitrogen Dioxide Data

The SD School Site began testing for Nitrogen Dioxide in 2008. The SD School Site is the second highest Nitrogen Dioxide concentration area in the state. There are only 3 parts per billion difference in annual concentration levels from the highest annual average of 7.3 parts per billion in 2015 to the lowest of 4.3 parts per billion in 2016. Trends show concentrations have a slight decrease at this site. Figure 10-27 shows the annual average for each of the years that data was collected. This parameter is meeting the goals of high concentration and population and will be continued.


Figure 10-27 – SD School Site – Nitrogen Dioxide Annual Averages



10.5.6 SD School Site Carbon Monoxide Data

The department operates just one Carbon Monoxide analyzer and it is located at our National Core site in Sioux Falls. A Carbon Monoxide analyzer was located at Union County #1 for a few years but has since been shut down. The SD School Site began testing for Carbon Monoxide in 2011. The Carbon Monoxide analyzer provides hourly concentration levels. The highest 8-hour average recorded at the SD School Site was 1.0 part per million in 2017. Trends show concentrations are steady at this site. Figure 10-28 shows the 8-hour average for each of the years that data was collected. This parameter is meeting the goals of high concentration and population and will be continued.

Figure 10-28 – SD School Site – Carbon Monoxide 8-hour averages



10.6 Fire Station #1 Site – Aberdeen Area

In 2019, one sampling site was operated in the city of Aberdeen at the Fire Station #1 Site. The Fire Station #1 Site was established in 2000 as part of the implementation of the PM_{2.5} air monitoring network. The parameters tested at the site include PM₁₀ and PM_{2.5}. The monitoring site was in the center of the city on top of the fire station roof just east of the main downtown business area. The area around the site has service type businesses, county and city offices, and residential area to the east. See Figure 10-29 for a picture of the monitoring site.

Figure 10-29 – Aberdeen’s Fire Station #1 Site



In 2009, Fire Station #1 was renovated, and a small addition was added to the south side of the building. The addition required no changes at the site so the location requirements in Title 40 of the Code of Federal Regulations Part 58 were still met. Table 10-7 contains details on the monitoring site specific to the requirements in Title 40 of the Code of Federal Regulations Part 58.

The Fire Station #1 site was closed at the end of 2019. A new site at the Aberdeen Bus Stop started sampling in 2020. Manual sampling will no longer be done at the new site and will instead be done with continuous monitors. This will result in a cost savings and the data will be displayed on our real-time data page and be sent to AirNow.


Table 10-7 – Fire Station #1 Site Specifics

Parameter	Information
Site Name	Fire Station #1
AQS ID Number	46-013-0003
Street Address	111 2 nd Ave SE, Aberdeen, SD
Geographic Coordinates	UTM Zone 14, NAD 83, E 540,216.92 N 5,034,545.94
MSA	None
PM₁₀	(Manual)
Sampler Type	Federal Reference Method RFPS-1298-126
Operating Schedule	Every 6 th Day
Scale Representation	Neighborhood
Monitoring Objective	High Concentration and Population
Sampling Method	Partisol 2000i
Analysis Methods	Gravimetric
Data Use	SLAMS (Comparison to the NAAQS),
PM_{2.5}	(Manual)
Sampler Type	Federal Reference Method RFPS-0498-117
Operating Schedule	Every 3 rd Day
Scale Representation	Neighborhood
Monitoring Objective	Population and High Concentration
Sampling Method	Partisol 2000i w/VSCC
Analysis Methods	Gravimetric
Data Use	SLAMS (Comparison to the NAAQS)

10.6.1 Fire Station #1 Site PM₁₀ Data

In 2009, the sampling schedule for PM₁₀ changed from every third day to every 6th day because concentrations at the site continued to be low. Figure 10-30 contains a graph of the annual averages since the site was setup in 2000.

Figure 10-30 – Fire Station #1 Site – PM₁₀ Annual Averages



The annual average concentrations change from year to year, but the trends line indicates a slight decrease in concentrations over the twenty years of testing. The annual averages range from a low of 14 micrograms per cubic meter in 2019 to a high concentration level of 25 micrograms per cubic meter recorded in 2018.

The PM₁₀ National Ambient Air Quality Standards is based on a 24-hour average concentration. The maximum 24-hour average concentration allowed is 150 micrograms per cubic meter. Attainment with the 24-hour standard is demonstrated when there is less than or equal to one expected exceedance per year averaged over three years. At the Fire Station #1 site in Aberdeen, there was one exceedance in 2018 with a 24-hour average of 533.7 micrograms per cubic meter. Since the manual monitor runs on a 1 in 6-day sampling schedule, this one exceedance caused the 3-year expected exceedance calculation of two.


The department believes the exceedance was caused by a natural event. According to the National Weather Service, “Leading up to the event, conditions were warm and generally dry in the James River Valley during May. Those conditions combined with strong winds from decaying thunderstorms in south central South Dakota to produce a dust storm. South winds of 50 to 80 mph kicked up a significant amount of dirt/dust as the winds moved north, leading to visibilities being reduced to below ¼ mile in many locations. The reduced visibilities caused a few traffic incidents and the winds knocked down trees, tree branches, and powerlines.” If not for the dust storm, this site would be attaining the PM₁₀ 24-hour standard.

When running the manual monitors on a 1 in 6-day schedule, having even one exceedance will cause a violation of the standard. The department evaluated switching from manual monitors to continuous monitors in Aberdeen to avoid a situation like this happening again. At the end of 2019, the Fire Station #1 site was closed and a new site at the Aberdeen Bus Stop was opened. Switching to a continuous monitor will result in a savings of time and money in the long run. With continuous monitors, the real time data will also be available to the public on the website.

10.6.2 Fire Station #1 Site PM_{2.5} Data

Sampling began for PM_{2.5} at this site in 2001. The PM_{2.5} monitors ran on an every third day sampling schedule. Annual averages for the Fire Station #1 Site in Aberdeen have ranged from 5.4 micrograms per cubic meter in 2016 to 9.0 micrograms per cubic meter in 2005. The trend line shows that annual average is declining in concentration level over the last 19 years. Figure 10-31 contains a graph of the annual average concentrations.

Figure 10-31 – Fire Station #1 Site – PM_{2.5} Annual Averages



The testing for this parameter is meeting the goals of high concentration and population and will be continued. However, because of continued industrial growth, to provide for the testing for other pollutants and to provide real time hourly data to the public, the Fire Station #1 site was closed at the end of 2019. A new site at the Aberdeen Bus Stop was opened in 2020.

10.7 Research Farm Site – Brookings Area

The Research Farm Site was setup in 2008 and is located at the Soil Conservation Farm northwest of the city of Brookings. An older site located at the City Hall building in the center of Brookings was discontinued at the end of 2014.

The Research Farm Site was set up in cooperation with the 3M Company in Brookings and Valero Renewable Fuels Company near the city of Aurora. The sampling for ozone was a requirement of the Prevention of Significant Deterioration permits for both facilities. The department operated the site and provided data to the facilities. The 3M Company completed their air monitoring report using the data for 2008. Valero Renewable Fuels Company decided not to complete the facility upgrade under its Prevention of Significant Deterioration permit and did not request any data from the Research Farm Site. Ozone data collected between 2008 and 2010 was added as a state and local air monitoring stations site to the National Database in 2010 and the site was continued, adding continuous PM_{10} and $PM_{2.5}$ in 2015.

The initial goals of the monitoring site were the evaluation of impacts to the ozone concentrations from modification at the 3M Company and Valero Renewable Fuels Company. The current goals are to collect ozone data downwind of a small city for comparison to the National Ambient Air Quality Standards and determine particulate matter data for a rural area in eastern South Dakota. The completion of the 2019 sampling year provides 12 years of testing and a better idea of trends for the ozone data. Figure 10-32 shows a current picture of the monitoring site.

Figure 10-32 –Research Farm Site



Table 10-8 contains details on the monitoring site specific to the requirements in Title 40 of the Code of Federal Regulations Part 58.


Table 10-8 –Research Farm Site Specifics

Parameter	Information
Site Name	Brookings Research Farm
AQS ID Number	46-011-0003
Street Address	3714 Western Ave.
Geographic Coordinates	UTM Zone 14, NAD 83, E 674766.316 N 4912930.911
MSA	None
Ozone	(Continuous)
Sampler Type	Federal Equivalent Method EQOA-0880-047
Operating Schedule	Every Day
Scale Representation	Regional
Monitoring Objective	High Concentration, Population, and Background
Sampling Method	Thermo 49i
Analysis Methods	ultraviolet
Data Use	SLAMS (Comparison to the NAAQS),
PM₁₀	(Continuous)
Sampler Type	Federal Equivalent Method EQPM-1102-150
Operating Schedule	Every Day
Scale Representation	Neighborhood
Monitoring Objective	High Concentration and Population
Sampling Method	Thermo 5014i BETA
Analysis Methods	Beta Attenuation
Data Use	SLAMS (Comparison to the NAAQS) Real-Time Data
PM_{2.5}	(Continuous)
Sampler Type	Federal Equivalent Method EQPM-0308-170
Operating Schedule	Every Day
Scale Representation	Neighborhood
Monitoring Objective	Population and High Concentration
Sampling Method	Met One BAM-1020
Analysis Methods	Beta Attenuation
Data Use	SLAMS (Comparison to the NAAQS) Real-Time Data

10.7.1 Research Farm Site PM₁₀ Data

PM₁₀ sampling began at this site in 2015. The annual average for this site ranged from 15 micrograms per cubic meter in 2016 to 19 micrograms per cubic meter in 2017. Testing for this parameter is meeting the goals of high concentration and population. Figure 10-33 contains a graph of the annual averages since the site was setup.


Figure 10-33 –Research Farm Site – PM₁₀ Annual Averages



10.7.2 Research Farm Site PM_{2.5} Data

PM_{2.5} sampling began at this site in 2015. The annual average for this site ranged from 5.9 micrograms per cubic meter in 2015 to 4.5 micrograms per cubic meter in 2016. Annual averages are well under the standard. Figure 10-34 contains a graph of the annual averages since the site was setup.

Figure 10-34 –Research Farm Site – PM_{2.5} Annual Averages




10.7.3 Research Farm Site Ozone Data

The 2019 sampling year is the twelfth ozone season of testing. The highest fourth highest 8-hour average for this site was at 0.071 parts per million in 2019. The SD School Site was the highest ozone concentration site in the state since 2010. In 2019, the Brookings Research Farm had the highest readings. There was a noticeable increase in concentration and in the number of high concentrations. EPA concurred these readings were out of the ordinary. The department received a new ozone analyzer and put it at the Brookings site to do a side by side comparison toward the end of October. The two analyzers tracked very well, but the new analyzer read 6-7 ppb lower. On October 30, the new analyzer was put into service and the Brookings' readings are more comparable to the other eastern sites. In 2020, an additional ozone analyzer was added in Watertown. This will expand our network along the entire eastern part of the state giving a better view of regional transport and another site to compare to the Brookings' readings. The ozone data trend indicates a slightly increasing level.

The testing for this parameter is meeting the goals of high concentration and population and will be continued. The graph in Figure 10-35 shows the yearly 4th highest ozone concentration levels for the last 12 years.

Figure 10-35 – Brookings Research Farm Site Ozone Yearly 4th Highest 8-Hour Averages



10.8 Watertown Site

In 2019, one sampling site was operated in the city of Watertown. Watertown is the fourth largest city in South Dakota with a population of 21,482. The city has an increasing growth rate and industrial base. The industrial base is a mixture of service-oriented business and light industry. One other air monitoring site was operated in Watertown starting in 1974 and closed 1987. Figure 10-36 shows a picture of the monitoring site.

Figure 10-36 – Watertown Site



The current Watertown Site was established in 2003 as part of the implementation of the PM_{2.5} network. In 2012, the manual PM_{2.5} monitors were replaced with a continuous monitor. Testing at the site includes the parameters of PM₁₀ and PM_{2.5} at a sampling frequency of every day. The monitoring site is in the western third of the city just east of an industrial park area. The site is located on City property in a monitoring shelter. The area around the site has service type businesses and light industry to the west and south. Residential areas are located to the north and east of the site. There have been no significant changes noted in buildings or trees around the site during this review. Table 10-9 contains details on the monitoring site specific to the requirements in Title 40 of the Code of Federal Regulations Part 58. An ozone analyzer was added to the site in 2020.

Table 10-9 – Watertown Site Specifics


Parameter	Information
Site Name	Watertown
AQS ID Number	46-029-0002
Street Address	801 4 th Ave. SW, Watertown, SD
Geographic Coordinates	UTM Zone 14, NAD 83, E 647,740.74 N 4,973,300.25
MSA	None
PM₁₀	(Continuous)
Sampler Type	Federal Equivalent Method EQPM-0798-122
Operating Schedule	Every Day
Scale Representation	Neighborhood
Monitoring Objective	High Concentration and Population
Sampling Method	Met One BAM-1020 Continuous
Analysis Methods	Beta Attenuation
Data Use	SLAMS (Comparison to the NAAQS) Real-Time Data

Parameter	Information
PM_{2.5}	(Continuous)
Sampler Type	Federal Equivalent Method EQPM-0308-170
Operating Schedule	Every Day
Scale Representation	Regional
Monitoring Objective	Background, Transport
Sampling Method	Met One BAM-1020 w/PM _{2.5} VSCC
Analysis Method	Beta Attenuation
Data Use	SLAMS (Comparison to the NAAQS) Real-time Data

10.8.1 Watertown Site PM₁₀ Data

The PM₁₀ monitor operated on an every third day sampling schedule until 2006 when a continuous PM₁₀ monitor replaced the manual monitors and an everyday sampling schedule began. The highest recorded annual average for PM₁₀ concentrations was 28 micrograms per cubic meter recorded in 2003. The lowest annual average concentration of 20 micrograms per cubic meter was recorded in 2005, 2011, 2013, 2014, 2015, and 2019. The annual average indicates concentration levels are slightly decreasing during the 17 years of testing. The PM₁₀ concentration can get close to and has exceeded the 24-hour standard. Testing for this parameter is meeting the goals of high concentration and population and will be continued. Figure 10-37 contains a graph of the annual averages.


Figure 10-37 – Watertown Site – PM₁₀ Annual Averages



10.8.2 Watertown Site PM_{2.5} Data

The PM_{2.5} monitors were run on an every third day schedule since the PM_{2.5} monitors were setup in 2003. Beginning in 2012, a continuous monitor was installed, and the site reported hourly concentrations on an everyday schedule. Annual averages for the Watertown Site range from a high of 11.0 micrograms per cubic meter in 2012 to a low of 4.5 micrograms per cubic meter in 2014. The annual average shows a decrease in PM_{2.5} concentration levels over the 17 years of testing. Testing for this parameter is meeting the goals of high concentration and population and will be continued. Figure 10-38 contains a graph showing the annual average concentration for each year of operation.

Figure 10-38 – Watertown Site PM_{2.5} Annual Averages



10.9 UC #1 Site – Union County

At the beginning of 2009, three new monitoring sites were set up in Union County. No ambient air quality testing had ever been completed in this county. All three sites are located north of Elk Point. The sampling goals for the new sites were to determine air pollution levels near the location of the proposed Hyperion Energy Center prior to construction, during construction, and post construction. The proposed project's Prevention of Significant Deterioration air quality permit has expired, no new application was submitted by the company and purchase easements on the property in Union County have all expired. By the end of 2013, the sites had collected five years of data so there is an adequate amount of data for use to show background levels and the difference in sampling locations for future use.

With no current project pending there is only need for one site to continue to show current levels in rural Union County. In 2012, the UC #3 Site was closed with the ozone parameter moved to the UC #1 Site. At the end of 2013, the UC #2 Site was closed because it was a duplicate site to the UC #1 Site. At the end of 2013, the Carbon Monoxide testing at UC #1 Site was discontinued because recorded concentrations were very low and there was no indication concentrations would ever get close to the standard level.

The UC #1 Site is located about 4 1/2 miles north of Elk Point. Sampling began just before January 1, 2009. The goals for the site are background and for comparison to the National Ambient Air Quality Standards. Figure 10-39 provides a picture of the monitoring site looking to the North. Table 10-10 contains details on the monitoring site specific to the requirements in Title 40 of the Code of Federal Regulations Part 58.

Figure 10-39 – UC #1 Site



Table 10-10 – UC #1 Site Specifics


Parameter	Information
Site Name	UC #1
AQS ID Number	46-127-0001
Street Address	31988 457 th Ave.
Geographic Coordinates	Lat. + 42.751518 Long. – 96.707208
MSA	Sioux City, IA-NE-SD

Parameter	Information
PM₁₀	(Continuous)
Sampler Type	Federal Equivalent Method EQPM-1102-150
Operating Schedule	Every Day
Scale Representation	Regional
Monitoring Objective	Background, Transport
Sampling Method	Thermo TA Series FH 62 C14 Continuous
Analysis Method	Beta Attenuation
Data Use	Real-time Data and SLAMS (Comparison to the NAAQS)
PM_{2.5}	(Continuous)
Sampler Type	Federal Equivalent Method EQPM-0308-170
Operating Schedule	Every Day
Scale Representation	Regional
Monitoring Objective	Background, Transport
Sampling Method	Met One BAM-1020 w/PM _{2.5} VSCC
Analysis Method	Beta Attenuation
Data Use	Real-time Data and SLAMS (Comparison to the NAAQS)
SO₂	(Continuous)
Sampler Type	Federal Equivalent Method EQSA-0486-060
Operating Schedule	Every Day
Scale Representation	Regional
Monitoring Objective	Background, Transport
Sampling Method	Instrumental 43i Trace Level Thermo
Analysis Methods	Pulsed Fluorescent
Data Use	Real-time Data and SLAMS (Comparison to the NAAQS)
NO₂	(Continuous)
Sampler Type	Federal Reference Method RFNA-1194-099
Operating Schedule	Every Day
Scale Representation	Regional
Monitoring Objective	Background, Transport
Sampling Method	Teledyne API T200
Analysis Method	Chemiluminescence
Data Use	Real-time Data and SLAMS (Comparison to the NAAQS)
Ozone	(Continuous)
Sampler Type	Federal Equivalent Method EQOA-0880-047
Operating Schedule	Every Day
Scale Representation	Regional
Monitoring Objective	Background, Transport
Sampling Method	Thermo 49i
Analysis Method	Ultraviolet
Data Use	Real-time Data and SLAMS (Comparison to the NAAQS)

10.9.1 UC #1 Site PM₁₀ Data

The annual average PM₁₀ concentrations at this site range from 15 micrograms per cubic meter in 2017 and 2019 to 22 micrograms per cubic meter in 2012. Trends indicate concentrations show a slight decrease for UC #1 Site. Testing for this parameter is meeting the goals and will be continued. See the annual averages for the UC #1 Site in Figure 10-40.


Figure 10-40 – UC #1 Site – Annual PM₁₀ Concentrations



10.9.2 UC #1 Site PM_{2.5} Data

The UC #1 Site continues to be one of the highest annual average and 24-hour locations in the state and in some years was the highest concentration site in the state. The trend line shows concentrations to be slightly decreasing over the ten years of testing. Testing for this parameter is meeting the goals and will be continued. See Figure 10-41 to view a graph of the annual averages.


Figure 10-41 –UC #1 Site – Annual PM_{2.5} Concentrations



10.9.3 UC #1 Site Sulfur Dioxide Data

Concentrations of Sulfur Dioxide follow the same trend as other sites in the state with many hourly average concentrations low near the detection level (0.1 parts per billion) for the analyzer method being used to collect the data. A trace level Sulfur Dioxide analyzer has operated at this site beginning in 2009. Trends indicate Sulfur Dioxide levels are dropping at this site. Testing for this parameter is meeting the goals and will be continued. See Figure 10-42 for a graph showing the 1-hour 99th percentile for this site.


Figure 10-42 –UC #1 Sulfur Dioxide 1-hour Concentrations



10.9.4 UC #1 Site – Nitrogen Dioxide Data

Concentrations of Nitrogen Dioxide follow the same trends as other rural areas in the state like the Badlands and Wind Cave sites. Annual average concentrations are very low near the detection level for the analyzer method being used to collect the data. Just as the Sulfur Dioxide parameter, the Nitrogen Dioxide parameter differences are noted from year to year when comparing a 1-hour average but the annual averages are very close in concentration. Trends indicate a slightly decreasing concentration level for UC #1 over the 11 years of testing. Testing for this parameter is meeting the goals and will be continued. Figure 10-43 shows a graph of the annual average concentrations for this site.


Figure 10-43 –UC #1 Site – Annual Nitrogen Dioxide Concentrations



10.9.5 UC #1 Site Ozone Data

The ozone 8-hour average for the UC #1 Site recorded a concentration that was similar to levels recorded at the Sioux Falls site in 2019. 2019 had an 8-hour average for this site of 0.064 parts per million. See Figure 10-44 for a graph of the ozone concentrations at the UC #1 Site. The trend is slightly increasing in concentration levels. Testing for this parameter is meeting the goals and will be continued.

Figure 10-44 – Union County #1 Site Ozone Concentrations



10.10 Pierre Airport Site

Pierre is the capital city of South Dakota. It is in the center of the state along the rough river bluffs overlooking the Missouri River. The population was 13,646 at the 2010 census. Pierre has a relatively dry, four-season climate with long, dry, cold winters, hot summers and brief spring and autumn transitions.

At the beginning of 2015, a new monitoring site was set up in Pierre. The site is located at the Pierre Regional Airport Industrial Park in northeast Pierre. The sampling goal for the new site was to test a new area of the state with no past PM_{2.5} monitoring. Figure 10-45 provides a picture of the monitoring site looking to the North. Table 10-11 contains details on the monitoring site specific to the requirements in Title 40 of the Code of Federal Regulations Part 58.

Figure 10-45 – Pierre Airport Site



Table 10-11 – Pierre Airport Site Specifics


Parameter	Information
Site Name	Pierre Airport
AQS ID Number	46-065-0003
Street Address	4293 Airport Road
Geographic Coordinates	Lat. + 44.373786 Long. – 100.287269
MSA	None

Parameter	Information
PM_{2.5}	(Continuous)
Sampler Type	Federal Equivalent Method EQPM-0308-170
Operating Schedule	Every Day
Scale Representation	Regional
Monitoring Objective	Background, Transport
Sampling Method	Met One BAM-1020 w/PM _{2.5} VSCC
Analysis Method	Beta Attenuation
Data Use	Real-time Data and SLAMS (Comparison to the NAAQS)

10.10.1 Pierre Airport Site – PM_{2.5} Data

2019 was the fifth year of monitoring at the Pierre Airport Site. The annual PM_{2.5} concentration at the site ranged from 4.5 micrograms per cubic meter in 2015 to 3.3 micrograms per cubic meter in 2019. The Pierre Airport Site shows relatively low concentrations, like those at the two National Parks sites. See Figure 10-46 to view a graph of the annual averages. Testing for this parameter is meeting the goals and will be continued.

Figure 10-46 – Pierre Airport Site – Annual PM_{2.5} Concentrations



11.0 SPECIAL AIR QUALITY MONITORING

11.1 PM_{2.5} Speciation Network

The PM_{2.5} Speciation Network quantifies mass concentrations and significant PM_{2.5} constituents which include trace elements, sulfate, nitrate, sodium, potassium, ammonium, and carbon. This series of analytes is very similar to those measured within the Interagency Monitoring of Protected Visual Environments program.

Physical and chemical speciation data are anticipated to provide valuable information for:

1. Assessing trends in mass component concentrations and related emissions, including specific source categories;
2. Characterizing annual and seasonal spatial variation of aerosols;
3. Determining the effectiveness of implementation control strategies;
4. Helping to implement the PM_{2.5} standard by using speciated data as input to air quality modeling analyses;
5. Aiding the interpretation of health studies by linking effects to PM_{2.5} constituents; and
6. Understanding the effects of atmospheric constituents on visibility impairment and regional haze.

South Dakota has one site that collects samples as part of the PM_{2.5} Speciation Network. This site is located at the SD School Site and collects 24-hour air samples on a 3-day schedule. The PM_{2.5} speciation monitor was moved from the KELO site to the SD School Site at the beginning of 2009. The SD School Site is located on the east central part of the city. The site is about 1.5 miles southeast of the main industrial area in Sioux Falls. The area around the site is mainly residential. Interstate 229 which is a major commuting road runs north and south about three city blocks east of the monitoring site. The predominant wind direction is northwest for most of the year with southeast winds during the summer months. Carbon samples were originally taken by the Met One SASS monitor. In September 2009, the Interagency Monitoring of Protected Visual Environments URG 3000N sampler was set up to do the carbon sampling. In November 2016, EPA Region 8 gave the department a Met One Super SASS monitor to replace the existing monitor.

At the beginning of 2016, a new lab was contracted to analyze and enter the data into EPA's Air Quality System. There is a lag in data entry and all the 2019 data has not yet been entered at the time this annual report was written. Therefore, the following graphs will only show data through 2018.

Figure 11-1 shows the average total organic carbon and elemental carbon concentrations for the URG monitor. Concentrations of carbon are low. The organic carbon concentrations are consistently higher than the elemental carbon. The average contribution of elemental carbon to the overall concentration remained about the same while organic carbon concentrations fluctuate. Although 2016 indicates the lowest concentration for total carbon levels in the ten years of testing, 2018 shows the highest.


Figure 11-1 – Average URG Monitor Total Carbon Concentrations



* The data did not meet the completeness requirements for 2016, 2017, 2018.

Figure 11-2 shows the average nitrate and sulfate concentrations analyzed from the PM_{2.5} samples. The graph shows trends for the concentration of nitrates and sulfates are declining overall with 2017 having the lowest concentrations during the sixteen years of testing in Sioux Falls.

Figure 11-2 – Average Nitrate and Sulfate Concentrations



* The data did not meet the completeness requirements for 2016

12.0 CONCLUSIONS

All areas in the state are in attainment of the federal National Ambient Air Quality Standards. The department is reviewing the option of submitting exceptional events packages for the dust storm in Aberdeen and the high wind events at the Rapid City Credit Union site. All sites meet the requirements of Title 40 of the Code of Federal Regulation, Part 58, Appendix A, C, D, and E.

The ambient air quality monitoring network is continually reviewed to ensure that there is adequate coverage of populated areas in the state as well as rural areas. As the state's population and industry changes, monitoring sites will be added or moved to new locations.

Major modifications to the sampling network include:

1. No major modifications to the sampling network are planned, unless the department is required to find new monitoring sites to replace the Rapid City Credit Union and/or Sioux Falls' SD School sites;
2. The Rapid City Library Site was closed at the end of 2019;
3. The Aberdeen Fire Station #1 Site was closed at the end of 2019 and a new Aberdeen Bus Stop Site was opened in 2020 to accommodate continuous monitoring; and
4. Before the 2020 ozone season, an ozone analyzer was added to the Watertown site.

Equipment Purchase Priorities include the following items:

1. Purchase a new shelter;
2. Continue to replace ESC 8816 and 8832 data loggers;
3. Continue to replace C series calibrators and analyzers;
4. Continue to replace equipment as needed to maintain the National Core site; and
5. Purchase new equipment as required to meet EPA requirements.

There is an ongoing effort to maintain staff training regarding the latest monitoring techniques and procedures to perform these studies. It is anticipated that the ambient air monitoring network will operate in much the same manner as it has in the past. This will include the identification of pollution problems, measurement and evaluation of the extent of the problem, and determination of action to be taken to protect the environment and the health of the people of South Dakota.

13.0 REFERENCES


1. Quality Assurance Handbook for Air Pollution Measurement Systems, Volume II, Ambient Air Monitoring Program, EPA-54/B-17-001, January 2017, located at <https://www3.epa.gov/ttn/amtic/files/ambient/pm25/qa/Final%20Handbook%20Document%2017.pdf>;
2. Title 40, Code of Federal Regulation, Part 50, located at <https://www.ecfr.gov/cgi-bin/text-idx?SID=52f340d421aa94fe820d7ba0d1eb1e28&mc=true&node=pt40.2.50&rgn=div5>;

3. Title 40, Code of Federal Regulation, Part 58, located at <https://www.ecfr.gov/cgi-bin/text-idx?SID=eb02812221844f2f21472cc2dd32fc0e&mc=true&node=pt40.6.58&rgn=div5>; and
4. SLAMS/NAMS/PAMS Network Review Guidance, EPA-454/R-98-003, March 1998, located at <https://www3.epa.gov/ttn/amtic/files/ambient/criteria/netrev98.pdf>.

Appendix A

AirNow Maps for 24-hour PM_{2.5} High Concentration Days


Figure A-1 – AirNow Map for 2/8/19



Appendix A

AirNow Maps for 24-hour PM_{2.5} High Concentration Days


Figure A-2 – AirNow Tech Map for 2/8/19



Appendix B

AirNow Maps for 24-hour PM₁₀ High Concentration Day


Figure B-1 - AirNow Map for 1/29/19



Appendix B

AirNow Maps for 24-hour PM₁₀ High Concentration Day


Figure B-2 - AirNow Tech Map for 1/29/29



Appendix B

AirNow Maps for 24-hour PM₁₀ High Concentration Day


Figure B-3 - AirNow Map for 2/14/19



Appendix B

AirNow Maps for 24-hour PM₁₀ High Concentration Day


Figure B-4 - AirNow Tech Map for 2/14/19



Appendix B

AirNow Maps for 24-hour PM₁₀ High Concentration Day


Figure B-5 - AirNow Map for 6/8/19



Appendix B

AirNow Maps for 24-hour PM₁₀ High Concentration Day


Figure B-6 – AirNow Tech Map for 6/8/19



Appendix C

AirNow Maps for 8-hour Average Ozone High Concentration Days


Figure C-1 - AirNow Map for 2/22/19



Appendix C

AirNow Maps for 8-hour Average Ozone High Concentration Days


Figure C-2 - AirNow Tech Map for 2/22/19



Appendix C

AirNow Maps for 8-hour Average Ozone High Concentration Days


Figure C-3 - AirNow Map for 2/23/19



Appendix C

AirNow Maps for 8-hour Average Ozone High Concentration Days


Figure C-4 - AirNow Tech Map for 2/23/19



Appendix C

AirNow Maps for 8-hour Average Ozone High Concentration Days


Figure C-5 - AirNow Map for 3/7/19



Appendix C

AirNow Maps for 8-hour Average Ozone High Concentration Days


Figure C-6 - AirNow Tech Map for 3/7/19



Appendix C

AirNow Maps for 8-hour Average Ozone High Concentration Days


Figure C-7 - AirNow Map for 3/10/19



Appendix C

AirNow Maps for 8-hour Average Ozone High Concentration Days

Figure C-8 - AirNow Tech Map for 3/10/19



Appendix C

AirNow Maps for 8-hour Average Ozone High Concentration Days


Figure C-9 - AirNow Map for 3/11/19



Appendix C

AirNow Maps for 8-hour Average Ozone High Concentration Days


Figure C-10 - AirNow Tech Map for 3/11/19



Appendix C

AirNow Maps for 8-hour Average Ozone High Concentration Days


Figure C-11 - AirNow Map for 3/16/19



Appendix C

AirNow Maps for 8-hour Average Ozone High Concentration Days


Figure C-12 - AirNow Tech Map for 3/16/19



Appendix C


AirNow Maps for 8-hour Average Ozone High Concentration Days

Figure C-13 - AirNow Map for 3/17/19



AirNow Maps for 8-hour Average Ozone High Concentration Days


Figure C-14 - AirNow Tech Map for 3/17/19



Appendix C

AirNow Maps for 8-hour Average Ozone High Concentration Days


Figure C-15 - AirNow Map for 3/18/19



Appendix C

AirNow Maps for 8-hour Average Ozone High Concentration Days


Figure C-16 - AirNow Tech Map for 3/18/19



Appendix C

AirNow Maps for 8-hour Average Ozone High Concentration Days


Figure C-17 - AirNow Map for 4/14/19



Appendix C

AirNow Maps for 8-hour Average Ozone High Concentration Days


Figure C-18 - AirNow Tech Map for 4/14/19



Appendix C

AirNow Maps for 8-hour Average Ozone High Concentration Days


Figure C-19 - AirNow Map for 4/25/19



Appendix C

AirNow Maps for 8-hour Average Ozone High Concentration Days


Figure C-20 - AirNow Tech Map for 4/25/19



Appendix C

AirNow Maps for 8-hour Average Ozone High Concentration Days


Figure C-21 - AirNow Map for 5/15/19



Appendix C

AirNow Maps for 8-hour Average Ozone High Concentration Days


Figure C-22 - AirNow Tech Map for 5/15/19



Appendix C

AirNow Maps for 8-hour Average Ozone High Concentration Days


Figure C-23 - AirNow Map for 5/29/19



Appendix C

AirNow Maps for 8-hour Average Ozone High Concentration Days


Figure C-24 - AirNow Tech Map for 5/29/19



Appendix C

AirNow Maps for 8-hour Average Ozone High Concentration Days


Figure C-25 - AirNow Map for 5/30/19



Appendix C

AirNow Maps for 8-hour Average Ozone High Concentration Days


Figure C-26 - AirNow Tech Map for 5/30/19



Appendix C

AirNow Maps for 8-hour Average Ozone High Concentration Days


Figure C-27 - AirNow Map for 5/31/19



Appendix C

AirNow Maps for 8-hour Average Ozone High Concentration Days


Figure C-28 - AirNow Tech Map for 5/31/19



Appendix C


AirNow Maps for 8-hour Average Ozone High Concentration Days

Figure C-29 - AirNow Map for 6/3/19



AirNow Maps for 8-hour Average Ozone High Concentration Days


Figure C-30 - AirNow Tech Map for 6/3/19



Appendix C

AirNow Maps for 8-hour Average Ozone High Concentration Days


Figure C-31 - AirNow Map for 6/4/19



Appendix C

AirNow Maps for 8-hour Average Ozone High Concentration Days


Figure C-32 - AirNow Tech Map for 6/4/19



Appendix C

AirNow Maps for 8-hour Average Ozone High Concentration Days


Figure C-33 - AirNow Map for 6/5/19



Appendix C

AirNow Maps for 8-hour Average Ozone High Concentration Days


Figure C-34 - AirNow Tech Map for 6/5/19



Appendix C

AirNow Maps for 8-hour Average Ozone High Concentration Days


Figure C-35 - AirNow Map for 6/6/19



Appendix C

AirNow Maps for 8-hour Average Ozone High Concentration Days


Figure C-36 - AirNow Tech Map for 6/6/19



Appendix C

AirNow Maps for 8-hour Average Ozone High Concentration Days


Figure C-37 - AirNow Map for 6/7/19



Appendix C

AirNow Maps for 8-hour Average Ozone High Concentration Days


Figure C-38 - AirNow Tech Map for 6/7/19



Appendix C

AirNow Maps for 8-hour Average Ozone High Concentration Days


Figure C-39 - AirNow Map for 6/8/19



Appendix C

AirNow Maps for 8-hour Average Ozone High Concentration Days


Figure C-40 - AirNow Tech Map for 6/8/19



Appendix C

AirNow Maps for 8-hour Average Ozone High Concentration Days


Figure C-41 - AirNow Map for 6/26/19



Appendix C

AirNow Maps for 8-hour Average Ozone High Concentration Days


Figure C-42 - AirNow Tech Map for 6/26/19



Appendix C

AirNow Maps for 8-hour Average Ozone High Concentration Days


Figure C-43 - AirNow Map for 6/29/29



Appendix C

AirNow Maps for 8-hour Average Ozone High Concentration Days


Figure C-44 - AirNow Tech Map for 6/29/19



Appendix C

AirNow Maps for 8-hour Average Ozone High Concentration Days

Figure C-45 - AirNow Map for 9/17/19



Appendix C

AirNow Maps for 8-hour Average Ozone High Concentration Days

Figure C-46 - AirNow Tech Map for 9/17/19

