


STATE OF SOUTH DAKOTA WELL DRILLERS REPORT

Location 1 1 Sec 2 Twp 3N Rg 4E

County

Lawrence

Please mark well location with an "X"



Well Completion Date 8-25-84

PROPOSED USE:

☒ Domestic ☐ Municipal ☐ Test Holes
☐ Irrigation ☐ Industrial ☐ Stock

Method of Drilling:

Cable Tool

WELL CONSTRUCTION:

Diameter of hole 6 inches Depth 50 feet

Casing: ☒ Steel ☒ Plastic ☐ Other

Specify

Pipe Weight 138 lb/ft 6 inches 0 feet 24 feet
1 lb/ft 6 inches 0 feet 24 feet

Was a well screen used? ☐ Yes ☒ No

If Not Specify 1/4" holes in 20' of plastic

Screen Type Slot Size

Length Diameter

Was Casing left open end? ☒ Yes ☐ No

Was a Packer or seal used? ☒ Yes ☐ No

If so what material? cement

Was well gravel packed? ☐ Yes ☒ No

Was well grouted? ☒ Yes ☐ No

Describe grouting procedure 3 sacks

2" thick sig. to 1 inch cement

To what depth? 24 Feet

What was grouting material? cement with

If cement, how many sacks? 3

Location of packer(s) and screen or perforated

pipe Bottom 20' of 5" plastic

pipe

WAS WELL PLUGGED OR ABANDONED ☐ Yes ☒ No

If so how and with what material?

Well Owner:

Name Don (P) Lane

Address H.C.R. 260 Norma S.D.

Well Log: Depth 577.5'

Formation From To

Barren and dark blue shale 0' 22'

Light brown soft shale 22' 32'

Hard brown shale with white quartz 32' 40'

unifed 40' 50'

Hard dark blue shale 40' 50'

STATIC WATER LEVEL 30 Feet

If flowing: closed in pressure PSI

GPM flow 20 through inch pipe

Controlled by ☐ Valve ☐ Reducers ☐ Other

If other; specify

Can well be completely shut off?

WELL TEST DATA:

☐ Pumped

☒ Bailed Describe: using 10 gal. bailer

☐ Other

Pumping Level Below Land Surface

34 ft. After 2 Hrs. pumped 20 GPM

 ft. After Hrs. pumped GPM

 ft. After Hrs. pumped GPM



This well was drilled under license # 305

and this report is true and accurate.

Don (P) Lane

Drilling Firm Signed by

8-29-84

Date

Mr. Lane
10-10-84