


STATE OF SOUTH DAKOTA WELL DRILLERS REPORT

Location SE 1/4 NW 1/4 Sec 34 Twp 50.5 N Rg 50-47 W

County

LincolnNorth
100Please mark well
location with
an "X"Well Completion Date 8-11-84

PROPOSED USE:

☒ Domestic ☐ Municipal ☐ Test Holes
☐ Irrigation ☐ Industrial ☐ Stock

Method of Drilling:

ROTARY

WELL CONSTRUCTION:

Diameter of hole 7 1/8 inches Depth 92 feetCasing: ☐ Steel ☒ Plastic ☐ Other

Specify _____

 Pipe Weight Diameter From To
200 lb/ft 5" inches 0 feet 89 feet
 _____ lb/ft _____ inches _____ feet _____ feet
Was a well screen used? ☒ Yes ☐ No

If Not Specify _____

Screen Type Johnson SS Slot Size 18Length 3' Diameter 5"Was Casing left open end? ☐ Yes ☒ NoWas a Packer or seal used? ☐ Yes ☒ No

If so what material? _____

Was well gravel packed? ☒ Yes ☐ NoWas well grouted? ☒ Yes ☐ NoDescribe grouting procedure GRAUTED 10' TO 30'To what depth? 30' FeetWhat was grouting material? PORTLAND CEMENTIf cement, how many sacks? 3Location of packer(s) and screen or perforated pipe 89' TO 90' SCREENWAS WELL PLUGGED OR ABANDONED ☐ Yes ☒ No

If so how and with what material? _____

Well Owner:

Name Bill Fink PRIAddress HARRISBURG

Well Log:

Formation

From

To

TOP SOIL05'CLAY5'12'SAND12'17'CLAY17'60'SANDY CLAY50'82'SAND82'90'STATIC WATER LEVEL 60' Ft

If flowing: closed in pressure _____ PSI

GPM flow _____ through _____ inch pipe

Controlled by ☐ Valve ☐ Reducers ☐ Other

If other; specify _____

Can well be completely shut off? _____

WELL TEST DATA:

☐ Pumped☐ Bailed☒ OtherDescribe: Developed with AIR

Pumping Level Below Land Surface

65' ft. After 3 Hrs. pumped 15 GPM

_____ ft. After _____ Hrs. pumped _____ GPM

_____ ft. After _____ Hrs. pumped _____ GPM

Remarks:

Well was drilled for a new house, there was no old well to plug.

This well was drilled under license # 239

and this report is true and accurate.

Drilling Firm Merriman DrillingSigned by John C. MerrimanDate 8-24-84

lth sent
9-24-84